

**Sunlite 05268-SU LED Emergency Light  
Fixture, 2.4 Watts, 120-277 Volt, Dual  
Heads, 90-Minute Battery Backup, Wall or  
Ceiling Mount, IP20, UL Listed, White**  
DUAL HEAD EMERGENCY LIGHT

**DESCRIPTION:**

*The Sunlite LED emergency light will help guide you to safety in the event of a power outage. Built-in back up batteries charge automatically when power is on and provide up to 90 minutes of light when the power is out. It features a flame-retardant, high impact thermoplastic housing molded in white. Each of the two lights can be positioned independently to provide optimum coverage. Built-in test switch and LED status indicator light. Bright 180 lumen output at 6500K daylight color temperature. Designed for wall or ceiling mounting on 120-277V service. UL Listed and CEC Title 20 compliant. IP20 rated.*



**FEATURES:**

- **EMERGENCY LIGHTING** - The Sunlite LED emergency light will help guide you to safety in the event of a power outage. They activate automatically and each of the two lights can be positioned independently to provide optimum coverage.
- **INTEGRATED LEDS** - With energy efficient LED technology built-in this is a maintenance free solution.
- **90 MINUTE BACK UP** - Built-in back up batteries charge automatically when power is on and provide up to 90 minutes of light when the power is out. Built-in test switch and LED status indicator light.
- **WALL OR CEILING MOUNT** - Designed for wall or ceiling mounting on 120-277V service. It features a flame-retardant, high impact thermoplastic housing molded in white.
- **SAFETY RATED** - UL Listed and CEC Title 20 compliant. IP20 rated.

## SPECIFICATIONS:

### General Characteristics

<b>Finish</b>	White
<b>Ingress Protection</b>	IP20 (12.5 mm solids, Not protected from liquids)
<b>Material</b>	Plastic
<b>Lens</b>	2 Head
<b>Lens Material</b>	Plastic

### Electrical Characteristics

<b>Watts</b>	2.4
<b>Volts</b>	120/277

### Light Characteristics

<b>Lumens Brightness</b>	180
<b>Color Rendering Index CRI</b>	70
<b>Color Temperature Kelvin</b>	6500K

### Fixture Characteristics

<b>Number of Lights</b>	2
<b>Mounting</b>	Wall
<b>Fixture Technology</b>	EXIT
<b>Use Location</b>	Indoor

### Additional Features

<b>Safety Rating Mark</b>	UL Listed - Damp Location
---------------------------	---------------------------

### Product Dimensions

<b>Item Dimension (in)</b>	(W) 10.11 (H) 4.29 (D) 3.46
<b>Package Dimension (in)</b>	(W) 4.65 (H) 13.75 (D) 5
<b>Package Weight (lb)</b>	0.04

### Product Data

<b>Case Unit Rate</b>	6
<b>Item UPC</b>	653703052687
<b>Warranty Years</b>	2

