

Sunlite 05271-SU Compact LED Exit Sign, 0.25 Watts, 120-277 Volt, 90-Minute Battery Backup, Universal Mount, IP20, UL Listed, White

DESCRIPTION:

The Sunlite LED exit sign will help guide you to an exit in the event of a power outage. Built-in back up batteries charge automatically when power is on and provide up to 90 minutes of illumination when the power is out. It features bright red illuminated EXIT letters and left and right directional arrow knock-outs. Flame-retardant, high impact thermoplastic housing molded in white. Designed for wall mounting on 120-277V service. UL Listed. IP20 rated. Meets or exceeds UL924 (21 separate tests), NEC, OSHA & NFPA 101 Life Safety Code requirements.

FEATURES:

- COMPACT EXIT SIGN The Sunlite LED exit sign will help guide you to an exit in the event of a power outage. It features bright red illuminated EXIT letters and left and right directional arrow knock-outs.
- INTEGRATED LEDS With energy efficient LED technology built-in this is a maintenance free solution.
- 90 MINUTE BACK UP Built-in back up batteries charge automatically when power is on and provide up to 90 minutes of illumination when the power is out. Built-in test switch and LED status indicator light.
- UNIVERSAL SURFACE MOUNT Designed for wall and ceiling mounting on 120-277V service. It features a flameretardant, high impact thermoplastic housing molded in white.
- SAFETY RATED UL Listed. IP20 rated. Meets or exceeds UL924 (21 separate tests), NEC, OSHA & NFPA 101 Life Safety Code requirements.





SPECIFICATIONS:

General Characteristics

Finish Material Application White Thermoplastic Commercial

Electrical Characteristics

 Watts
 0.25

 Volts
 120/277

Fixture Characteristics

MountingUniversalFixture TechnologyEXITUse LocationIndoor

Additional Features

Safety Rating Mark UL Listed - Damp Location

Product Dimensions

Package Dimension (in)
Package Weight (lb)

Product Data

Case Unit Rate Item UPC

(W) 2.45 (H) 12.25 (D) 8

1.2

6

653703052717

