

**Features**

**Housing**

Die-formed Cold-rolled Steel  
Finish Options: -30 Oil Rubbed Bronze, -06 White, -62 Satin Nickel

**Optical**

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity  
LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

**Electrical**

High Power Factor, Low THD

**Lamp**

Built-in LED Module  
MCT Type: Get Preferable Fixture Color Temperature by Slide Switch on LED Board  
Color Temperature Option – 3000K, 3500K, 4000K

**Certifications**

ETL/cETL Listed, Suitable for Damp Locations

**Warranty**

5 Years Warranty on Driver and LED Module



**LED Type**

Model	Input Voltage	Input Voltage	LED CT	Lumen (Typ)	Finish	Dimension (OD X H)	Energy Star
2-0245D-A-xxxxK	120V	17W	3000K / 3500K / 4000K / 5000K	1600	White	11.0" x 3.3"	Yes
2-0246D-A-xxxxK	120V ~ 277V	24W	3000K / 3500K / 4000K / 5000K	2560	White	14.0" x 3.6"	Yes
2-0240D-06-xxxxK	120V	12W	3000K or 4000K	780	White	11.0" x 3.3"	Yes
2-0241D-MCT-06	120V	25W	3000K, 3500K, 4000K	1600	White	14.0" x 3.6"	Yes
2-0242D-MCT-06	120V	25W	3000K, 3500K, 4000K	1700	White	16.0" x 4.0"	---