

2-0245D-G 2-0246D-G

Ceiling Fixture & Pendant



Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

Lamp

LED Type: Built-in (Color Temperature Option – 3000K or 4000K or MCT Type)

MCT: Multiple Color Temperature (3000K/3500K/4000K)

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light.

Certification

ETL/cETL Listed

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Wattage	LED CT	Lumen (TYP)	Finish	Shade	Dimension (OD X H)
2-0245D-G-xxxxK-05/22	120V ~ 277V	17W	3000K or 4000K	1060	Black / Gold	Acrylic	14.5" x 4.0"
2-0246D-G-xxxxK-05/22	120V ~ 277V	24W	3000K or 4000K	1450	Black / Gold	Acrylic	17.5" x 4.0"
2-0245D-G-PD-xxxxK-05/22	120V ~ 277V	17W	3000K or 4000K	1060	Black / Gold	Acrylic	14.5" x 11.0"
2-0246D-G-PD-xxxxK-05/22	120V ~ 277V	24W	3000K or 4000K	1450	Black / Gold	Acrylic	17.5" x 11.0"