

# 2-0245 2-0246 2-0247

## Round Puff Ceiling Fixture



### Features

#### Housing

Die-formed Cold-rolled Steel  
 Finish Options: -62 satin Nickel, -30 Oil Rubbed Bronze

#### Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity  
 LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

#### Electrical

JA8 Type: High Power Factor (>0.98), Low THD (< 10%), Min. Dimming Level (3%)

#### Lamp


LED Type: Built-in (More Color Temperature Option – 3500K, 5000K)  
 CFL Type: T9 Circline or GU24 CFL Lamp (Color Temperature Option – 2700K, 4000K)  
 JA8 Type: 60,000 Hours Rating (LM80, TM21), Flicker Free Meets JA10 Standard

#### Certifications

UL/cUL, ETL/cETL Listed, Suitable for Damp Locations  
 JA8 Type: CEC Listed

#### Warranty

5 Years Warranty on Driver and LED Module



### LED Type

Model	Input Voltage	Input Voltage	LED CT/CRI	Lumen (Typ)	Dimension (OD X H)	Energy Star
2-0245D-9W-xxxxK	120V	9W	3000K / >80	1000	11.0" x 4.3"	Yes
2-0245D-xxxxK	120V	17W	3000K / >80	1600	11.0" x 4.3"	Yes
2-0246D-xxxxK	120V ~ 277V	24W	3000K / >80	2560	14.0" x 4.6"	Yes
2-0247D-xxxxK	120V ~ 277V	35W	3000K / >80	3280	18.9" x 4.6"	---

### CFL Type

Model	Input Voltage	Shade	Lamp	Dimension (OD X H)	Energy Star
2-0245PG-123	120V	Opal Acrylic	1 x 23W GU24	11.0" x 4.3"	---
2-0246PG-213	120V	Opal Acrylic	2 x 13W GU24	14.0" x 4.6"	---
2-0247-2232	120V	Opal Acrylic	22W+32W T9 Cir.	18.9" x 4.6"	---

### JA8 Type

Model	Input Voltage	Input Voltage	LED CT/CRI	Lumen (Typ)	Dimming	Dimension (OD X H)
2-0247D (JA8)	120V ~ 277V	38W	3000K / >90	3280	0-10V	18.9" x 4.6"