



## FEATURES & SPECIFICATIONS

**INTENDED USE** A shallow economy designed wrap around high efficiency luminaire available in either two or four foot lengths. Low initial cost, maintenance free, this series also delivers excellent brightness control.

**SIZE** W x L x H in inches (mm)

9.375W x 48L x 3.1Dp (4ft.)

### CONSTRUCTION

Completely die formed from heavy gauge cold rolled steel. Design embossed ends are locked and secures to the housing. Wireway cover snaps on or off without tools.

### MOUNTING

Suitable for individual or continuous run installations. May be surface or pendant mounted.

### Typical Options and Accessories

EM - Emergency battery backup, WP - whips.

### DIFFUSERS

A crystal clear diffuser extruded from 100% virgin acrylic that will maintain its color under normal conditions, indefinitely. Linear prisms on the interior side walls direct the light ceilingwards, which can then refract back down. The bottom is composed of an evenly spaced pattern of conical prisms yielding low brightness, glarefree diffused light. Diffuser is lift and shift for ease of relamping and cleaning and is capable of hanging down from either side of the housing.

## ORDERING INFORMATION

Example: 209A24LF28W2700LDMV40K

## 209 2ft

### STANDARD

| 209           | A                               | 24L         | F28W3400L  | DMV   | 40K  |
|---------------|---------------------------------|-------------|--|---|--|
| <b>Series</b> |                                 | <b>Size</b> | <b>Wattage and Lumen</b>   | <b>Driver</b>   | <b>Kelvin Temperature</b>  |
| 209           |                                 | 24L 24"     | <b>F12W1600L</b> 12 System Watts,<br>1665 Delivered Lumens<br><br><b>F18W2400L</b> 18 System Watts,<br>2420 Delivered Lumens<br><br><b>F24W3100L</b> 24 System Watts,<br>3135 Delivered Lumens<br><br><b>F28W3400L</b> 28 System Watts,<br>3465 Delivered Lumens<br><br><b>F30W3600L</b> 30 System Watts,<br>3630 Delivered Lumens | <b>DMV</b> 0-10V Dimming<br>* Field installed-Dimming Wire<br><br><b>DMVFID</b> 0-10V Dimming<br>* Factory installed-Dimming Wire | <b>30K</b> 3000K<br><b>35K</b> 3500K<br><b>40K</b> 4000K<br><b>50K</b> 5000K |
|               | <b>Lens</b>                     |             |  |   |  |
|               | A Prismatic Acrylic #12 Pattern |             |  |   |  |

\* Consult Factory for more options



|                 |
|-----------------|
| Catalog Number: |
| Notes:          |

## 209 4ft

Example: 209A48LF32W3450LDMV40K

### STANDARD

|                      |  |                        |  |   |  |
|----------------------|--|------------------------|--|---|--|
| 209                  | A  | 48L                    | F32W3450L  | DMV   | 40K  |
| <b>Series</b><br>209 | <b>LENS</b><br>A Prismatic Acrylic #12 Pattern | <b>Size</b><br>48L 48" | <b>Wattage and Lumen</b>   | <b>Driver</b>   | <b>Kelvin Temperature</b>  |
|                      |  |                        | <b>F23W2650L</b> 23 System Watts,<br>2650 Delivered Lumens<br><b>F32W3450L</b> 32 System Watts,<br>3818 Delivered Lumens<br><b>F48W4800L</b> 48 System Watts,<br>5107 Delivered Lumens<br><b>F57W5400L</b> 57 System Watts,<br>6019 Delivered Lumens | <b>DMV</b> 0-10V Dimming<br>*Field installed-Dimming Wire<br><b>DMVFID</b> 0-10V Dimming<br>*Factory installed-Dimming Wire | <b>30K</b> 3000K<br><b>35K</b> 3500K<br><b>40K</b> 4000K<br><b>50K</b> 5000K |

### HIGH OUTPUT

|                      |  |                        |  |   |  |
|----------------------|--|------------------------|--|---|--|
| 209                  | A  | 48L                    | H72W7000L  | DMV   | 40K  |
| <b>Series</b><br>209 | <b>LENS</b><br>A Prismatic Acrylic #12 Pattern | <b>Size</b><br>48L 48" | <b>Wattage and Lumen</b>                                   | <b>Driver</b>   | <b>Kelvin Temperature</b>  |
|                      |  |                        | <b>H72W7000L</b> 72 System Watts,<br>7000 Delivered Lumens | <b>DMV</b> 0-10V Dimming<br>*Field installed-Dimming Wire<br><b>DMVFID</b> 0-10V Dimming<br>*Factory installed-Dimming Wire | <b>30K</b> 3000K<br><b>35K</b> 3500K<br><b>40K</b> 4000K<br><b>50K</b> 5000K |

\* Consult Factory for more options



### DIMENSIONS

All dimensions are inches. Specifications subject to change without notice.

