

3-4121

Wall Mount / Ceiling Mount, Outdoor



Features

Housing

Die-cast Aluminum with Powder Coated Finish
Finish Option: -06 White, -08 Gray

Optical

Electrical

Built-in Photo Cell Option

Lamp

LED Type: Integrate LED Module, More Color Temperature Option 3500K, 5000K
GU24 CFL Bulb Type: More Color Temperature Option 2700K, 4000K

Certification

UL/cUL, ETL/cETL Listed, Suitable for Wet Locations

Warranty

5 Years Limited Warranty on Driver and LED



LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Finish / Shade	Dimension (H x W X E)	Energy Star
3-4121D-05-3000K	120V ~ 277V	22W	3000K / 80	1300	Black / PC	13.0"OD x 3.8"H	Yes
3-4121D-05-4000K	120V ~ 277V	22W	4000K / 80	1360	Black / PC	13.0"OD x 3.8"H	Yes

GU24 CFL Type

Model	Input Voltage	Finish	Lamp	Shade	Dimension (H x W X E)	Energy Star
3-4121-05	120V	Black	2 x 13W GU24	Opal Polycarbonate	13.0"OD x 3.8"H	