

3-4310

Wall Mount / Ceiling Mount, Outdoor



Features

Housing

Die-Cast Aluminum with Powder Coated Finish or Stainless Steel
 Finish Option: -06 White, -08 Gray, -03 Stainless Steel

Optical

Diffuser: Opal Polycarbonate

Electrical

120V, Built-in Photo Cell Option

Lamp

LED Type: Integrate LED Module, More Color Temperature Option 3500K, 5000K
 GU24 CFL Bulb Type: More Color Temperature Option 2700K, 4000K

Certification

UL/cUL, ETL/cETL Listed, Suitable for Wet Locations

Warranty

5 Years Limited Warranty on Driver and LED



LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Housing/Finish	Dimension (H x W X E)	Energy Star
3-4310D-05-3000K	120V	15W	3000K / 80	1120	Die Cast Aluminum /Black	14.1" x 10.0" x 5.7"	Yes
3-4310D-05-4000K	120V	15W	4000K / 80	1176	Die Cast Aluminum /Black	14.1" x 10.0" x 5.7"	Yes
3-4310D-03-3000K	120V	15W	3000K / 80	1120	Stainless	14.1" x 10.0" x 5.7"	Yes
3-4310D-03-4000K	120V	15W	4000K / 80	1176	Stainless	14.1" x 10.0" x 5.7"	Yes

GU24 CFL Type

Model	Input Voltage	Finish	Lamp	Housing/Finish	Dimension (H x W X E)	Energy Star
3-4310-05	120V	Black	2 x 13W GU24	Die Cast Aluminum /Black	14.1" x 10.0" x 5.7"	