

3-4311

Wall Mount, Outdoor



Features

Housing

Die-formed Cold-rolled Steel with Powder Coated Finish
Finish Options: -05 Black, -06 White (GU24 CFL Type Only)

Optical

Electrical

120V, Built-in Photo Cell Option

Lamp

Integrate LED Module: More Color Temperature Option 3500K, 5000K
GU24 CFL Bulb Type: More Color Temperature Option 2700K, 4000K

Certification

UL/cUL, ETL/cETL Listed, Suitable for Wet Locations

Warranty

5 Years Limited Warranty on Driver and LED



LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Housing / Shade	Dimension (H x W X E)	Energy Star
3-4311D-05-3000K	120V	15W	3000K / 80	1150	Steel / Glass	9.1" x 6.7" x 4.4"	Yes
3-4311D-05-4000K	120V	15W	4000K / 80	1200	Steel / Glass	9.1" x 6.7" x 4.4"	Yes

GU24 CFL Type

Model	Input Voltage	Finish	Lamp	Shade	Dimension (H x W X E)	Energy Star
3-4311-118-05	120V	Black	1 x 18W GU24	Frosted Glass	9.1" x 6.7" x 4.4"	Yes
3-4311-123-05	120V	Black	1 x 23W GU24	Frosted Glass	9.1" x 6.7" x 4.4"	Yes