## G25 4.5W FILAMENT DIM. TITANIUM LED SERIES



PRO



- Silver bowl redirects light prevents glare
- High efficacy 89 LPW in Soft White
- Micro-designed driver No heatsink required
- Comfortable warm diffused light
- Vintage globe look fits all applications
- Smooth dimming with existing installations

















\$113 Savings per lamp\*













## FILAMENT PRODUCT FEATURES



The GREEN CREATIVE Filament Series features a wide variety of vintage style bulbs that use the latest in LED technology. Each filament bulb uses a high quality LED package which results in longer lifetimes and higher efficacies. Each lamp's micro-designed driver provides excellent dimming performance without the need for a heat sink.

## G25 4.5W FILAMENT DIM. TITANIUM LED SERIES









## **SPECIFICATIONS**

Product Model         97826           Model         4.5FQ25DIM/827/SB           Type         G25           Base         E26           Power (W)         4.5           Voltage - Frequency         120V 60Hz           Color Temp. (ANSI)         Soft White 2700K           CRI (Ra)         82           Typical lumens (Im)         400           Efficacy (LPW)         89           Beam Angle         N.A.           Dimmable         Yes**           Power Factor         0.9           Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15*x4.41* (80x112mm)           Weight (lb. / g)         0.11lb. / 50g		
Base         E26           Power (W)         4.5           Voltage - Frequency         120V 60Hz           Color Temp. (ANSI)         Soft White 2700K           CRI (Ra)         82           Typical lumens (Im)         400           Efficacy (LPW)         89           Beam Angle         N.A.           Dimmable         Yes**           Power Factor         0.9           Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15*x4.41" (80x112mm)		
Power (W)         4.5           Voltage - Frequency         120V 60Hz           Color Temp. (ANSI)         Soft White 2700K           CRI (Ra)         82           Typical lumens (Im)         400           Efficacy (LPW)         89           Beam Angle         N.A.           Dimmable         Yes**           Power Factor         0.9           Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15"x4.41" (80x112mm)	Туре	G25
Voltage - Frequency         120V 60Hz           Color Temp. (ANSI)         Soft White 2700K           CRI (Ra)         82           Typical lumens (Im)         400           Efficacy (LPW)         89           Beam Angle         N.A.           Dimmable         Yes**           Power Factor         0.9           Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15"x4.41" (80x112mm)	Base	E26
Color Temp. (ANSI)         Soft White 2700K           CRI (Ra)         82           Typical lumens (Im)         400           Efficacy (LPW)         89           Beam Angle         N.A.           Dimmable         Yes**           Power Factor         0.9           Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15"x4.41" (80x112mm)	Power (W)	4.5
CRI (Ra)         82           Typical lumens (Im)         400           Efficacy (LPW)         89           Beam Angle         N.A.           Dimmable         Yes**           Power Factor         0.9           Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15"x4.41" (80x112mm)	Voltage - Frequency	120V 60Hz
Typical lumens (Im)         400           Efficacy (LPW)         89           Beam Angle         N.A.           Dimmable         Yes**           Power Factor         0.9           Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15"x4.41" (80x112mm)	Color Temp. (ANSI)	Soft White 2700K
Efficacy (LPW)         89           Beam Angle         N.A.           Dimmable         Yes**           Power Factor         0.9           Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15"x4.41" (80x112mm)	CRI (Ra)	82
Beam Angle         N.A.           Dimmable         Yes**           Power Factor         0.9           Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15"x4.41" (80x112mm)	Typical lumens (Im)	400
Dimmable         Yes**           Power Factor         0.9           Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15"x4.41" (80x112mm)	Efficacy (LPW)	89
Power Factor         0.9           Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15"x4.41" (80x112mm)	Beam Angle	N.A.
Rated Lifetime - L70 (hrs.)         25,000           Dia. x MOL         3.15"x4.41" (80x112mm)	Dimmable	Yes**
<b>Dia. x MOL</b> 3.15"x4.41" (80x112mm)	Power Factor	0.9
Cita XIII.	Rated Lifetime - L70 (hrs.)	25,000
Weight (lb. / g) 0.11lb. / 50g	Dia. x MOL	3.15"x4.41" (80x112mm)
	Weight (lb. / g)	0.11lb. / 50g

<sup>\*</sup> Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$2 incandescent with 1000-hr lifetime, \$16 LED with 25,000-hr lifetime

<sup>\*\*</sup> List of tested dimmer switches available on website
\*\*\* Suitable for damp locations. Not for use where directly exposed to weather or water