



JOB NAME: CAT#: TYPE:

APPLICATIONS

Give your facility a clean and sleek look with this LED premium strip. This fixture is sure to enhance any environment, provide energy savings, and give better quality lighting. This fixture is cost effective and makes this perfect for: schools, retail, warehouse, storage or any other facility area currently using strip fixtures.

FEATURES & BENEFITS

- Extruded frosted acrylic Lens
- Available in 24", 48", and 96" (2', 4', & 8') lengths
- Easy assembly and maintenance
- L₇₀> 60,000 hrs.



DIMENSIONS

W x L x H in inches

24 in: 4.25"W x 24.00"L x 3.25"H 48 in: 4.25"W x 48.00"L x 3.25"H 96 in: 4.25"W x 96.00"L x 3.25"H











JOB NAME: CAT#: TYPE:

ORDERING

EXAMPLE: 44FSF 24 LED 18 DMV FR 30

44FSF	LED
-------	-----

1. SERIES	2. LENGTH	3. GEAR	4. WATTAGE/LUMENS	5. DRIVER	6. LENS	7. COLOR TEMP
44FSF LED Premium Lensed Strip	24 24" long48 48" long96 96" long	LED	24 in. 18			30 3000K 35 3500K 40 4000K 50 5000K
			96 in. 48			

8. EMERGENCY (O)1

E84

Emergency Battery Pack 10W ~1300 Lumens

9. SENSOR (O)1

OS Occupancy Sensor

OSD Occupancy Sensor w/ daylight harvesting and dimming

SSM Integral microwave sensor

10. CORD & WHIP (O)1

CS 6' cord 18/3

WP 6' whip 3 wire MC

*See cord & whip ordering chart below

*Cord & Whip Ordering Chart (Add to End of Fixture Part Number)								
Part No.	# of Wires	Length	End Fitting	Finish	Voltage	Amps (TL Only)		
WP - Whip CS - Cordset	(Blank) 3 Wire 4 - 4 Wire 5 - 5 Wire 6 - 6 Wire	(Blank) 6 feet 8 - 8 feet 10 - 10 feet 12 - 12 feet 15 - 15 feet	(Blank) No Plug P* - Standard Plug TL* - Twist Lock	BK - Black WH - White	(Blank) 120-277V 120 - 120V 277 - 277V 347 - 347V 480 - 480V	15 - 15 Amps 20 - 20 Amps		

ACCESSORIES

A144-2 (2)V-hooks and (2) 2 ft chains

Notes:

¹(O) is optional

Lumens are subject to a tolerance of $\pm 10\%$ and not relevant to RGB Input wattage can vary depending on options Dimensions and specifications subject to change without notice.







