

624ST 636ST 648ST T5ST

T8 & T5HO Lamp Strips



Features

Housing

Die-formed Cold-rolled Steel

Optical

Without Shade

Electrical

120V ~ 277V High Power Factor Ballast

Lamp

T8 or T5HO Lamp

True Color Temperature: 3000K, 4000K or 5000K

Certification

UL/cUL, ETL/cETL Listed



CFL Type

Model	Input Voltage	Input Wattage	Lamp	Dimension (L X W X H)
648ST-132 HPF	120V ~ 277V	29W	1 x F32 T8, 32W	48.00" x 2.80" x 3.40"
624ST-217 HPF	120V ~ 277V	34W	2 x F17 T8, 17W	24.00" x 4.40" x 3.40"
636ST-225 HPF	120V ~ 277V	50W	2 x F25 T8, 25W	36.00" x 4.40" x 3.40"
648ST-232 HPF	120V ~ 277V	58W	2 x F32 T8, 32W	48.00" x 4.40" x 3.40"
T5ST-124	120V ~ 277V	24W	1 x F24 T5HO, 24W	22.38" x 1.38" x 1.25"
T5ST-139	120V ~ 277V	39W	1 x F39 T5HO, 39W	34.25" x 1.38" x 1.25"
T5ST-154	120V ~ 277V	54W	1 x F54 T5HO, 54W	46.12" x 1.38" x 1.25"
T5ST-224	120V ~ 277V	48W	2 x F24 T5HO, 24W	22.38" x 2.38" x 1.25"
T5ST-239	120V ~ 277V	78W	2 x F39 T5HO, 39W	34.25" x 2.38" x 1.25"
T5ST-254	120V ~ 277V	108W	2 x F54 T5HO, 54W	46.12" x 2.38" x 1.25"

T8 LED Tube Type - with DLC Listed T8 LED Tube

Model	Input Voltage	Input Wattage	T8 LED Tube	Tube Lumen (TYP)	Dimension (L X W X H)
624STD-20W	120V ~ 277V	20W	2 x 10W	2200	24.0" x 4.4" x 3.4"
648STD-36W	120V ~ 277V	36W	2 x 18W	4000	48.0" x 4.4" x 3.4"
648STD-44W	120V ~ 277V	44W	2 x 22W	5000	48.0" x 4.4" x 3.4"

T8 LED Tube Type - with DLC Listed T8 LED Tube

Model	Input Voltage	Input Wattage	T5 LED Tube	Tube Lumen (TYP)	Dimension (L X W X H)
T5ST-56W	120V ~ 277V	62W	Ballast Compatible	6000	46.12" x 2.38" x 1.25"