

624STD1 648STD1



LED Strip

Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

Built Emergency Back Up Light & Bi-level Dimming

Lamp

Integrate LED Module with High CRI

Certification

ETL/cETL Listed, Suitable for Damp Locations, DLC Listed



LED Strip

Model	Input Voltage	Input Wattage	Lumen (TYP)	LED CT	CRI	Dimension (L X W X H)	DLC
624STD1-HE-4000K	120V ~ 277V	23W	2380	4000K	>80	24.0" x 4.4" x 3.3"	Standard
624STD1-HE-5000K	120V ~ 277V	23W	2500	5000K	>80	24.0" x 4.4" x 3.3"	Standard
648STD1-HE-36W-4000K	120V ~ 277V	36W	3960	4000K	>80	48.0" x 4.4" x 3.3"	Standard
648STD1-HE-36W-5000K	120V ~ 277V	36W	4160	5000K	>80	48.0" x 4.4" x 3.3"	Standard
648STD1-HE-48W-4000K	120V ~ 277V	46W	5060	4000K	>80	48.0" x 4.4" x 3.3"	Standard
648STD1-HE-48W-5000K	120V ~ 277V	46W	5300	5000K	>80	48.0" x 4.4" x 3.3"	Standard
624STD1-VHO-4000K	120V ~ 277V	14W	1800	4000K	>80	24.0" x 4.4" x 3.3"	Premium
624STD1-VHO-5000K	120V ~ 277V	14W	1900	5000K	>80	24.0" x 4.4" x 3.3"	Premium
648STD1-VHO-36W-4000K	120V ~ 277V	32W	4150	4000K	>80	48.0" x 4.4" x 3.3"	Premium
648STD1-VHO-36W-5000K	120V ~ 277V	32W	4220	5000K	>80	48.0" x 4.4" x 3.3"	Premium

Bi-Level Lights - With Built-in High Frequency Sensor

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L X W X H)
648STD1-HE-36W-Bi-xxxxK	120V ~ 277V	36W	4000K or 5000K	>80	3960	48.0" x 4.4" x 3.3"
648STD1-HE-48W-Bi-xxxxK	120V ~ 277V	46W	4000K or 5000K	>80	5060	48.0" x 4.4" x 3.3"
648STD1-VHO-36W-Bi-xxxxK	120V ~ 277V	36W	4000K or 5000K	>80	4150	48.0" x 4.4" x 3.3"

624STD1 648STD1

LED Strip



With Built-in Emergency Back Up

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L X W X H)
648STD1-HE-36W-EM-xxxxK	120V ~ 277V	36W	4000K or 5000K	>80	3960	48.0" x 4.4" x 3.3"
648STD1-HE-48W-EM-xxxxK	120V ~ 277V	46W	4000K or 5000K	>80	5060	48.0" x 4.4" x 3.3"
648STD1-VHO-36W-EM-xxxxK	120V ~ 277V	36W	4000K or 5000K	>80	4150	48.0" x 4.4" x 3.3"

With Built-in Emergency Back Up & Bi-Level Lights

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L X W X H)
648STD1-HE-36W-EM-Bi-xxxxK	120V ~ 277V	36W	4000K or 5000K	>80	3960	48.0" x 4.4" x 3.3"
648STD1-HE-48W-EM-Bi-xxxxK	120V ~ 277V	46W	4000K or 5000K	>80	5060	48.0" x 4.4" x 3.3"
648STD1-VHO-36W-EM-Bi-xxxxK	120V ~ 277V	36W	4000K or 5000K	>80	4150	48.0" x 4.4" x 3.3"