


Type:
Project:
Comments:
Prepared By:

Part #	8102HAQ-NB			
Category #:	8102			
Family:	Recessed			
Product Category:	Recessed Down Light			
Description:	6" Airtight Incandescent Recessed Down Light w/ out socket bracket			
Design Features				
Connectors	3 part quick connectors pre installed in all J Boxes			
Construction	New construction			
Thermal Protection	Protected against misuse of insulation and improper wiring			
IC Rating	IC rated for direct contact with non cellulose type insulation			
J Box	Listed for feed through wiring (4 in-4 out) and seven ½" knockouts			
Bar hangers	Pre installed allowing for position at any point w/in a 24" joist span. Can be turned 90° on plaster frame, & to fit T-bar spine w/out additional clamps for use in drop ceilings.			
Nails	Pre installed captive nails on bar hangers			
Wattage	Up to 90W			
Voltage	120V-60Hz			
Warranty	1 year limited warranty			
Lamp	A19, PAR30/38, BR30/38, LED retro			
Listing				
ETL/UL	ETL and cETL certified for damp location			
Meets Washington's S	tate energy code for restricted airflow			





"Designed for use with trims that have integral socket brackets and designed to be contractor friendly for *quick installation*."







## **Trim Options**

	Туре	Item#	Finishes	O.D.
	Shower, Lexan, Fresnel Lens 40W Max, A19	8502FS-BR	Wet location listed Socket Bracket Included	8"
	Lexan Flat Opal Albalite Lens 60W Max, A19	8505AL-BR	Wet location listed Socket Bracket Included	8"
0	Eyeball 75W Max, PAR30/BR30	8506	Black and white	8"
	Shower Trim w/Lexan Drop Opal Lens 60W Max, A19	8509DR-BR		8"
0	Regressed Eyeball, w/White Baffle 75W Max PAR30/BR30	8516	Airtight White	8"
	Cone, Baffle 100W Max PAR30/BR30/A19 PAR38/BR40	8519	Airtight Finishes: BK, WH	8"
	Baffle, White w/Clear Reflector 75W Max PAR30/BR30	8534	Airtight White	8"
	Reflector 75W Max PAR30/BR30	8535	Clear	8"
9	Open Trim w/Socket Bracket 75W Max, PAR30/BR30	8544	White	8"

## **Additional Information**

- 1. Socket is adjustable for proper positioning of different lamps types.
- 2. Adjusts to fit up to 1-1/4" ceiling thickness.
- 3. 7-1/2" height allows use in 2" x 8" joist construction.