


| Type: |
|--------------|
| Project: |
| Comments: |
| Prepared By: |

| Part # | 8104HICA | | | |
|---|--|--|--|--|
| Category #: | 8104 | | | |
| Family: | Recessed | | | |
| Product Category: | Recessed Down Light | | | |
| Description: | 6" Shallow Incandescent IC rated housing | | | |
| Design Features | | | | |
| Connectors | 3 part quick connectors pre installed in all J Boxes | | | |
| Construction | New construction | | | |
| Thermal Protection | Protected against misuse of insulation and improper wiring | | | |
| IC Rating | IC rated for direct contact with non cellulose type insulation | | | |
| J Box | Listed for feed through wiring (4 in-4 out) and seven ½" knockouts | | | |
| Bar hangers | Pre installed allowing for position at any point w/in a 24" joist span. Can be turned 90° on plaster frame, & to fit T-bar spine w/out additional clamps for use in drop ceilings. | | | |
| Nails | Pre installed captive nails on bar hangers | | | |
| Wattage | Up to 75W | | | |
| Voltage | 120V-60Hz | | | |
| Warranty | 1 year limited warranty | | | |
| Listing | | | | |
| ETL/UL | cULus certified for damp location | | | |
| Meets Washington's State energy code for restricted airflow | | | | |











Trim Options

| | Туре | Item# | Finishes | O.D. |
|----|--|--------|--|------|
| | Shower, Lexan, Fresnel Lens 60W Max, A19 | 8502FS | Wet location listed Metal trim ring available | 8" |
| | Baffle 75W Max PAR30/BR30 | 8504 | Black Optional BA, BK rings | 8" |
| | Lexan Flat Opal Albalite Lens 40W Max, A19 | 8505AL | Wet location listed Metal trim ring available | 8" |
| 0 | Eyeball, 75W Max, PAR30/BR30 | 8506 | Brushed aluminum, black and white | 8" |
| 0 | Open Trim, 75W Max PAR30/BR30 | 8508 | Brushed aluminum & white | 8" |
| 9 | Lexan Drop Opal 60W, A19 | 8509DR | Wet location listed Metal trim ring available | 8" |
| | Baffle 75W Max PAR30/BR00 | 8511 | Brushed aluminum, oil rubbed bronze, and white Optional BA, BK rings | 8" |
| | Reflector, Specular 75W Max PAR30/BR30 | 8513 | Brushed aluminum and clear Optional BA, BK rings | 8" |
| 0 | Regressed Eyeball, w/Baffle 75W Max PAR30/BR30 | 8516 | White Airtight | 8" |
| | Wall Wash 60W Max, A19 | 8517WW | White | 8" |
| | Fresnel Lens w/White Baffle 40W Max, A19 | 8522 | White | 8" |
| 10 | Wall Wash w/Reflctor 60W Max, A19 | 8527 | Clear and white | 8" |
| | Regressed Drop Opal w/White Baffle 40W Max, A19 | 8537 | Wet location listed White | 8" |

| Gimbal 75W Max, PAR30 | 8540 | Brushed aluminum, white & black | 8" |
|--------------------------|------|---------------------------------|----|
| Splay 40W Max, A19 | 8546 | White | 8" |

Additional Information

- 1. Socket is adjustable for proper positioning of different lamps types.
- 2. Adjusts to fit up to 1-1/4" ceiling thickness.
- 3. 5-1/2" height allows use in 2" x 6" joist construction.