

Sunlite 85135 2x2 FT LED Flat Panel Troffer Light, Lay-in Fixture, 30 Watts, 3750 Lumens, 3500K-Neutral White, 120-277V, Dimmable, 50,000 Hour Life Span, Energy Star Rated, UL & DLC Approved

DESCRIPTION:

The Sunlite 2x2 Troffer Panel Fixture is an excellent addition to any environment. It features a slim design metal body with white trim and a shatter-resistant frosted lens. Output is a bright 3750 lumens while only using 30 watts of electricity. High color rendering at 80 CRI. This dimmable fixture has a 50,000-hour life span and is ETL Listed for damp location installation (IP20). Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates. Fixture Measurements: H-2.75" W: 24" D: 24"

FEATURES:

-
-
-
-
-



SPECIFICATIONS:

General Characteristics

Bulb Shape	Integrated LED
Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Dimming Percentage	10%-100%
Material	Aluminum
Lens	Center Basket
Lens Finish	White
Bulb Type	Integrated

Electrical Characteristics

Watts	30
Volts	120-277
LED Chip Manufacturer	LG 5630 + ESPEN driver

Light Characteristics

Lumens Brightness	3750
Color Rendering Index CRI	80
Emitted Color	Neutral White
Color Temperature Kelvin	3500K

Fixture Characteristics

Style	Troffer
Shape	Square
Number of Lights	1
Mounting	Recessed
IC Rating	Yes
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	UL Listed - Damp Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Number	PLEYXCGM0QX3
DLC Classification	Premium

Product Dimensions

Size	2X2
Item Dimension (in)	(W) 24 (H) 2.75 (D) 24
Package Dimension (in)	(W) 24.68 (H) 3.15 (D) 25.6
Package Weight (lb)	10.14

Product Data

Item UPC	653703851358
Warranty Years	5



ACCESSORIES:



Catalog # 85138-SU
2X2