

Sunlite 88907-SU LED Dual-Head Round Wall Mount Flood Light Fixture With Motion Sensor, 20 Watts, 120 Volts, 1800 Lumen Output, Round Lights, IP65 Rated, ETL Listed, 50K - Super White, Black Finish

DESCRIPTION:

Sunlite LED Round Wall Mount Floodlight fixtures provide ample illumination for all outdoor spaces. Dual heads can be adjusted individually to optimize coverage area. Built-in motion sensor activates lights when movement is detected. With a bright 1800 lumen output at 5000K Super White color temperature they are an energy efficient solution for your lighting needs. Each fixture uses only 20 watts with a low estimated yearly energy cost of \$2.41. (Based on 3 hours/day use at \$0.11/kWh) Ideal for security and entryway lighting in residential or commercial locations. Long life, LED technology built-in means no bulbs to replace and up to 35,000 hours of maintenance-free service. ETL Listed for wet location installation and IP65 rated.

FEATURES:

- LED TECHNOLOGY Sunlite LED Round Wall Mount Floodlight fixtures provide ample illumination for all outdoor spaces. Each fixture contains 48 high output LEDs and dual heads that can be adjusted individually to optimize coverage area.
- ENERGY EFFICIENT Each fixture uses only 20 watts of energy. Estimated yearly energy cost is a low \$2.41. (Based on 3 hours/day use at \$0.11/kWh) With a 35,000 hour lifespan these fixtures will provide significant savings in electricity over their lifetime and require no maintenance.
- BUILT-IN MOTION SENSOR Built-in motion sensor activates lights when movement is detected.
- SECURITY AND ENTRYWAY LIGHTING Each fixture contains 48 LEDs and gives off a bright 1800 lumen output with 5000K Super White color temperature. Ideal for security and entryway lighting in residential or commercial installations.
- ETL LISTED These fixtures are ETL Listed for wet location installation. They operate on 120 volt service.





sunlite

SPECIFICATIONS:

General Characteristics

Average Life Span Years

Average Rated Hours

Ingress Protection

Finish

Dimmable

Lens Material

Lens Finish

Material

35000InBlackF32FIP65 (Dust-tight solids, Water
jets)CNoCAluminum & PlasticFPolycarbonateCClearF

Product Dimensions

Item Dimension (in)	(W) 6.34 (H) 9.25 (D) 7.6
Package Dimension (in)	(W) 9 (H) 8.2 (D) 6.9
Package Weight (lb)	1.950
Canopy Width (in)	4.2
Canopy Height (in)	1.5

Product Data

Case Unit Rate	6
Item UPC	653703889078
Warranty Years	2

Electrical Characteristics

20
120
SMD2835
0.9
20°C-45°C

Light Characteristics

Lumens Brightness	1800
Color Rendering Index CRI	80
Emitted Color	Super White
Color Temperature Kelvin	5000K
Flicker	60°

Fixture Characteristics

Shape	Rectangular
Number of Lights	2
Mounting	Wall
Fixture Technology	LED
Use Location	Outdoor

Additional Features

Safety Rating Mark	ETL Listed - Wet Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes

