

iBright LED Batten Fixture



Product Description

The iBright LED Batten Fixture is ATG's newest addition to its indoor lighting selection. With a sleek and contemporary design, the iBright LED Batten Fixture is ideal for application in conference rooms, offices, reception areas, and retail stores. The Batten Fixture offers two mounting options, a surface mount or a suspension rope, as well as two finish colors, black or white aluminum, to optimize on the look and feel of the room.

Features

- 100LM/W efficacy
- Maintenance Free & Environmentally Friendly (No Mercury Used)
- Dusk-To-Dawn And Occupancy Control Compatible
- IES LM80 Tested LED
- LM79 Data & IES Files Available
- Title 24 Compliant
- DLC Product Code: PXFNEJQU

Project Name:

Date:

Prepared By:

Notes:

Construction

Constructed with sturdy extrusion aluminum. Frosted lens is fitted on the luminaire for glare prevention and maximized brightness.

Finish

Luminaire coated in an environmentally friendly polyester powder formulated for a durable and long-lasting color in a white and black finish. No toxic heavy metals, VOC, or mercury were used in the design of this product.

Installation

Suitable for surface mount with a bracket or suspension by the means of rope.

Testing and Certifications

All luminaires have been tested by an independent laboratory in accordance with IESNA LM79 and LM80. Product certifications include: DLC, ETL, Title 24, RoHS, Lighting Facts, and Safety Listing.

Options, Accessories and Controls

Luminaire is compatible with most of the 1-10V dimming systems in the market and KO sensor.

Lifespan and Warranty

Industry-leading L70 rated lifetime of over 63,000 hours with ATG's guaranteed five (5) year warranty.


Ordering Information:

Typical Order Example: AESLF-40K-4FT-00


Family series	CCT	Size	Options
AESLF= Batten fixture	30K=3000K 35K=3500K 40K=4000K 50K=5000K	4FT=4feet	XXXX*

*X=0-9, A-Z or blank

Model	Wattage	Input Voltage	Lm Efficacy	Lm Flux	CRI	Color Temp	Power Factor	THD	L70Life time	Size
AESLF-40F-4FT	40W	100~277VAC	98Lm/W	4000LM	84	4000K	>0.90	<15%	63,000H	4FT
AESLF-50F-4FT	40W	100~277VAC	102Lm/W	4000LM	84	5000K	>0.90	<15%	63,000H	4FT
Finish Color		Housing		Lens Type		Certification		Warranty		
White &Black		Aluminum & PC		Frosted		DLC, ETL		5 Years		



Luminous Intensity Distribution



877.461.5333



sales@atgelectronics.com



www.atgelectronics.com