




JOB NAME: CAT#: TYPE:

## **APPLICATIONS**

Now bring your exterior applications to life with a special designed wet location linear pendant. This aluminum extrusion is 3.5" wide for a bold yet minimal look with a sealed lens to keep out moisture and bugs.


### **FEATURES & BENEFITS**

- Aluminum 6063, good heat radiation with long lifespan
- Waterprrof IP66
- Anti-Collision LEvel IK10
- Support 0-10V, PWM and resistor dimming solution
- Hight lighting efficiency
- · Long lifespan, >50,000 hours
- Light sources adopts LM-80 certified LED
- Adopt UL Class P certified power supply





## **DIMENSIONS**



2456mm(96.7")

Dimensions and specifications subject to change without notice.



# All in One Channel Wet Location

JOB NAME: CAT#: TYPE:

### **ORDERING**

EXAMPLE: AIOCSW-48LED45DMVSA30

| AIOCSW    |                      | LED |                   |                       |           |               |           |        |               |       |
|-----------|----------------------|-----|-------------------|-----------------------|-----------|---------------|-----------|--------|---------------|-------|
| 1. SERIES | RIES 2. SIZE 3. GEAR |     | 4. WATTAGE/LUMENS |                       | 5. DRIVER |               | 6. FINISH |        | 8. COLOR TEMP |       |
| AIOCSW    | <b>48</b> 48"        | LED |                   | 48"                   | DMV       | 0-10V Dimming |           | White  | 30            | 3000k |
|           | <b>96</b> 96"        |     | 45                | 45 Watts 5000 Lumens  |           | 120-277VAC    | SA        | Silver | 40            | 4000K |
|           |                      |     |                   | <u>96"</u>            |           | Multivolt     | ВК        | Black  | 50            | 5000K |
|           |                      |     | 90                | 90 Watts 10300 Lumens |           |               |           |        |               |       |

#### **ACCESSORIES**

AIOC5WMFH¹ Wiring Harness 5" to Join 2 Channels
AIOCJOINER-SA Mechanical Joiner to Join 2 AIOCSA

Channels AIOCSURF<sup>1</sup>

Surface Mount Screw and Toggle Set of 3

(Includes 24 Inch Power Cord)

A-HCPF606WH5W<sup>2</sup> Pendant Mounting Power Feed Canopy Kit

5 Wire For Up To 6' Drop

**A-HCPF612WH5W**<sup>2</sup> Pendant Mounting Power Feed Canopy Kit

5 Wire For Up To 12' Drop

A-HCNPF606WH Pendant Mounting Non-Power Canopy Kit, 6'

Cable With Canopy

A-HCNPF612WH Pendant Mounting Non-Power Canopy Kit

12' Cable With Canopy

Lumens are subject to a tolerance of ±10% and not relevant to RGB Input wattage can vary depending on options

Dimensions and specifications subject to change without notice.

Dimensions and specifications subject to change without notice.

<sup>&</sup>lt;sup>1</sup>Included with channels only need to purchase for replacements

<sup>&</sup>lt;sup>2</sup>Use one power feed canopy kit for every power drop. Non-power feed version is ordered separately for mounting where no power feed is required