



PROJECT:


TYPE:

LOCATION:

CAT:



Dark Bronze



White

Description

The Panorama Sunset Series offers effective lumen output while maintaining its low wattage energy consumption. Built from durable UV resistant materials which ensure maintenance-free operation over its long 50,000 hour rated life.

Features

- Die-cast, UV resistant powder coated aluminum housing with tempered glass lens and molded gasket with silicone seal
- 1/2" NPS plugs compatible with dusk to dawn photocell accessory
- Adjustable swivel arm
- cULus Listed, IP65 (wet location)
- 50,000 hours rated life

Mounting

Line-voltage; Includes universal mounting bracket with ground wire terminal for secure wall mount installation

Applications

Architectural and Security Lighting

Warranty

3 years




Packaging

Retail Box



Technical Information


Model	ALV3-2H		ALV3-1H	
	White	Dark Bronze	White	Dark Bronze
Finish				
Voltage	120V AC			
CCT	3000K			
CRI	80+			
Wattage	24W		12W	
Lumens	2000Lm		1000Lm	
Beam Angle	2 x 95°		95°	
Tilt	105°		180°	
Dimming	N/A			
Rating	cULus, wet locations, RoHS Compliant			
Rated Life	50,000 Hours			





Ordering Information

120V AC
Panorama Sunset



Panorama Sentry Flood Lights Include:
(1) LED Flood light fixture
(1) Mounting bracket with ground wire terminal

Example Part # **AL-1PIR-WH**



Additional Information

For a rain-tight seal, apply silicone caulking around the perimeter of the housing where it contacts the mounting surface

NOTES



AMERICAN LIGHTING WARRANTY

LIMITED WARRANTY FOR LED PRODUCTS: 3 YEARS

LIMITED PRODUCT WARRANTY

Our products are warranted to be free from defects in material and workmanship for the warranty period listed. Warranty periods begin from the date of shipment from American Lighting Inc's warehouse to the original purchaser. Products that prove to be defective during their specific warranty period will be either repaired or replaced, at the sole discretion of American Lighting Inc. Claims for defective products must be submitted in writing to American Lighting Inc's RGA Department within the warranty period. Upon approval of such return, American Lighting Inc reserves the right to inspect the product for misuse or abuse. Claims for indirect or consequential damages or for product that, in American Lighting Inc's opinion, has been misused will be denied. This is a warranty of product reliability only and not a warranty of merchantability or fitness for a particular purpose. American Lighting Inc shall have no liability whatsoever in any event for payment of incidental or consequential damages, including, without limitations, installation costs and/or damages for personal injury and/or property. These products may represent a possible shock or fire hazard if improperly installed or altered in any way. This warranty does not apply to any product that has not been properly installed in accordance with current local codes and/or the National Electrical Code. Products that require a transformer, driver, or power supply must be used in conjunction with American Lighting Inc's recommended power supply to ensure safety and retain product warranty.

PRODUCT SPECIFICATIONS

For the latest product information, updates, instructions and details concerning specifications, colors, finishes, performance, installation and design, visit www.americanlighting.com. Color may vary from the color printed herein due to limitations in photographic and printing processes. American Lighting Inc. reserves the right to change product specifications without notice. Other product specifications such as color temperature, wavelength characteristics and lumen output are subject to production limitations and may vary. LED technology is changing rapidly, and not all color temperatures and performance levels can be duplicated at a later time. Best practices include purchasing 10-15% more for a particular project on the same initial order where white LED color temperatures must be maintained over project and product life. Eventual product replacement should be considered at layout and design stages. Best practices also include testing connections and product performance prior to mounting and/or installing.

AVERAGE LIFE

Average incandescent lamp life, rated life and average life are terms used to describe the number of hours at which half of the lamps have failed. For LEDs, the hours of rated life specify the point where 70% of original lumen output is reached. Below this point, the effective life is over, however, the LED may still emit light. Individual results may vary with actual environmental conditions including, but not limited to, proper installation, ambient temperature and/or input voltage fluctuations.