



# Puck Lighting ATHENA



- Super thin recessed light requiring only minimal space
- Only 3W power consumption
- Smooth light
- Lifetime: 50,000 hours (ta= 77°F, 25°C)
- Ta: -4°F~95°F (-20°C~35°C)
- Material: Aluminum alloy



## Dimensions: (inches/mm)



## Wiring Diagram



How to order using our catalog numbers:  
Example: ATHENA-30K90SS

Series	Color Temp	Beam Angle	Finish	Installation
ATHENA	30K - 3000K 40K - 4000K	90 - 90°	S - Silver SS - Stainless steel	S - Screw Mounting

Catalog No.	Model	Description					Max. Pcs Per LED Power Supply 40W (NA159-4024LA-12A6)
		Rated Input	Ra	Wattage	Luminous Flux (TYP@4000K)	Included	
ATHENA-30K90SS	ATHENA-S36-24V	24VDC	85	3W	330lm	1pc LED fixture 2pcs Screws	11 pcs
ATHENA-40K90SS							
ATHENA-30K90SSS							
ATHENA-40K90SSS							

# Puck Lighting ATHENA

## How to choose your driver & cables:

Catalog No.	Description	Photo
NA159-4024LA-12A6	Model: SLT40-24VL-UN-A Input: 120-240VAC NA plug 1 + 59" cable. Output: 24VDC 12-way splitter JB-12A + 6" cable.	

\*Note: For alternative driver configurations, please contact our sales department.

Vertical & Horizontal Beamwidth			Center Beam FC	
			3000K	4000K
			2274	2274
0.3	0.50	1011	1011	
0.45	0.75	568	568	
0.6	1.00	364	364	
0.75	1.25	330lm	330lm	
H (m)	D (m)			

## Installation

