



- 7/9 watts
- 400-750 lumens
- 60-80 lpw
- replaces 40/60W incandescent

features

- Cost-effective LED solution for replacing 40W and 60W standard incandescent A lamps
- 80% more efficient and 30x longer life than standard incandescent
- Natural A-lamp smooth body appearance
- Available in both dimmable and non-dimmable versions
- Instant-On with no warm up, unlike CFLs
- Choice of 2700K, 3000K, 4000K, and 5000K CCT
- Acceptable for ICAT rated downlights
- Shatter-resistant for reduced risk of injury and breakage



performance

- 7W/420 LM replaces 40W incandescent
- 9W/750 LM replaces 60W incandescent
- Long life: 25,000 hours
- Standard series 80+ CRI for enhanced color and lighting uniformity from lamp to lamp
- 120V @ 60Hz
- 240° beam angle
- Operating temperature range from -4°F (-20°C) to 104°F (40°C)
- ANSI construction compliant
- Not for use with electronic timers, photocells, motion/occupancy sensors, or in totally enclosed luminaires

applications

- Ceiling and pendant fixtures
- Floor and table lamps
- Wall sconces
- Downlights

- 25,000 LIFETIME HRS
- CRI (Ra)
- INSTANT ON
- 3 YR WARRANTY
- SHATTER RESISTANT

dimensions



ordering information

Litespan Part #	Order Code	Watts	Lumens	CCT	CRI	Beam Angle	MOL	Base	Life Hours	Replaces Incandescent
LED7WA19/240/827K-DIM-G4A	90035	7W	400	2700K	80+	240°	4.41"	E26	25,000	40W A19
LED7WA19/240/830K-DIM-G4A	90033	7W	420	3000K	80+	240°	4.41"	E26	25,000	40W A19
LED7WA19/240/840K-DIM-G4A	90031	7W	420	4000K	80+	240°	4.41"	E26	25,000	40W A19
LED7WA19/240/850K-DIM-G4A	90029	7W	420	5000K	80+	240°	4.41"	E26	25,000	40W A19
LED9WA19/240/827K-DIM-G4A	90018	9W	700	2700K	80+	240°	4.41"	E26	25,000	60W A19
LED9WA19/240/830K-DIM-G4A	90017	9W	750	3000K	80+	240°	4.41"	E26	25,000	60W A19
LED9WA19/240/840K-DIM-G4A	90016	9W	750	4000K	80+	240°	4.41"	E26	25,000	60W A19
LED9WA19/240/850K-DIM-G4A	08571	9W	750	5000K	80+	240°	4.41"	E26	25,000	60W A19
LED7WA19/240/827K-DIM-G5A*	08885	7W	400	2700K	80+	240°	4.41"	E26	25,000	40W A19
LED7WA19/240/830K-DIM-G5A*	08886	7W	420	3000K	80+	240°	4.41"	E26	25,000	40W A19
LED7WA19/240/840K-DIM-G5A*	08887	7W	420	4000K	80+	240°	4.41"	E26	25,000	40W A19
LED7WA19/240/850K-DIM-G5A*	08888	7W	420	5000K	80+	240°	4.41"	E26	25,000	40W A19
LED9WA19/240/827K-DIM-G5A*	08889	9W	700	2700K	80+	240°	4.41"	E26	25,000	60W A19
LED9WA19/240/830K-DIM-G5A*	08890	9W	750	3000K	80+	240°	4.41"	E26	25,000	60W A19
LED9WA19/240/840K-DIM-G5A*	08891	9W	750	4000K	80+	240°	4.41"	E26	25,000	60W A19
LED9WA19/240/850K-DIM-G5A*	08892	9W	750	5000K	80+	240°	4.41"	E26	25,000	60W A19

*Available Q4 2015

watch > like > follow



selection. solutions. simplicity. eiko.com

23220 W. 84th St, Shawnee, KS 66227 · (P) 1.800.852.2217 (F) 1.800.492.8975
Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 (F) 1.888.705.1335