

BH1

Outdoor Light



Features

Housing

Injection Molding with Polycarbonate
Ideal for Harsh Environment Applications

Optical

Shade: Injection Molding with Polycarbonate
LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

LED Driver: High Power Factor (> 0.95), Low THD (< 20%)
Compatible with Triac Dimmer
Photo Cell Option (Order Code: -PC)

Lamp

LED Type: Integrate LED Module
GU24 Type: GU24 CFL Bulb, More Color Temperature Option 2700K, 4000K

Certification

UL/cUL, ETL/cETL Listed, Wet Location Rated

Warranty

5 Years Limited Warranty on Driver and LED



LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Energy Efficiency (lm/Watt)	Dimension (L x W x H)	Energy Star
BH1D-4000K	120V	12W	4000K / > 80	1100	92.8	9.2" x 5.0" x 4.3"	Yes
BH1D-5000K	120V	12W	5000K / > 80	1100	92.8	9.2" x 5.0" x 4.3"	Yes

GU24 Type

Model	Input Voltage	Input Wattage	Housing/Shade	Lamp	Dimension (L x W x H)	Energy Star
BH1PG-118	120V	18W	Opal PC	1 x 18W GU24	9.2" x 5.0" x 4.3"	