

# KZXTEU

# THIN DIE-CAST ALUMINUM EXIT SIGN



STANDARD



## ILLUMINATION

Ultra bright, energy efficient, long life Red or Green LEDs.

### ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 2.4V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

#### MOUNTING

- Aluminum mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

#### HOUSING


- Premium-grade, aluminum housing (also available in optional black or white powder-coated finishes).
- Field selectable knockout Chevron directional indicators.
- Quick-snap face plate closure.
- Specification-grade, low profile, thin aluminum die-cast design.
- Available in single or double face only.

#### ORDERING INFORMATION

#### WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C 50°C).
- Certified to CEC under Title 20 Regulations.

#### DIMENSIONS



#### Sample Part Number: KZXTEU1RW

| MODEL  |   | No. of FACES | LETTER COLOR |       | HOUSING COLOR |          | BATTERY |                |
|--------|---|--------------|--------------|-------|---------------|----------|---------|----------------|
| KZXTEU | 1 | Single Face  | R            | Red   | W             | White    | (blank) | AC-Only        |
|        | 2 | Double Face  | G            | Green | В             | Black    | EM      | Battery Backup |
|        |   |              |              |       | Α             | Aluminum |         |                |