

C137 C138

Ceiling Fixture



Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

Electrical

High Power Factor, Low THD

Lamp

Built-in LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light
Color Temperature Option – 3000K, 3500K, 4000K, 5000K

Certifications

ETL/cETL Listed

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Voltage	LED CT/ CRI	Lumen (Typ)	Dimension (L X W X H)	Finish	Energy Star
C137D-62-3000K	120V ~ 277V	18W	3000K / 80	1650	15.3" x 15.3" x 3.4"	Satin Nickel / Acrylic	Yes
C137D-62-4000K	120V ~ 277V	18W	4000K / 80	1750	15.3" x 15.3" x 3.4"	Satin Nickel / Acrylic	Yes
C138D-62-3000K	120V ~ 277V	35W	3000K / 80	2450	19.3" x 19.3" x 3.8"	Satin Nickel / Acrylic	Yes
C138D-62-4000K	120V ~ 277V	35W	4000K / 80	2650	19.3" x 19.3" x 3.8"	Satin Nickel / Acrylic	Yes