

# C4048D C5048D P4048D P5048D

## Ceiling Fixtures, Pendant



### Features

#### Housing

Die-formed Cold-rolled Steel and Aluminum Extrusion  
 Finish Option: -06 White, -60 Brushed Aluminum, -05 Black

#### Electrical

High Power Factor, Low THD

#### Lamp

Built-in Module (Color Temperature Option – 3000K, 4000K)  
 LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

#### Certification

ETL/cETL Listed, Suitable for Damp Locations

#### Warranty

5 Years Warranty on Driver and LED Module



### LED Type

Model	Input Voltage	Input Wattage	CRI	Lumen (TYP)	CT	Finish	Shade	Dimension (OD X H x H1)	Energy Star
C5048D-xxxxK-05	120V-277V	17W	> 80	1600	3000K or 4000K	Black	Clear Glass	6.0" x 9.0"	---
C4048D-xxxxK-05	120V-277V	14W	> 80	1200	3000K or 4000K	Black	Clear Glass	4.8" x 7.8"	---
P5048D-xxxxK-05	120V-277V	17W	> 80	1600	3000K or 4000K	Black	Clear Glass	6.0" x 9.1" x 6.0'	---
P4048D-xxxxK-05	120V-277V	14W	> 80	1200	3000K or 4000K	Black	Clear Glass	4.8" x 7.8" x 6.0'	---

H1: 6', Hanging Cable Length ,Adjustable