

PROJECT NAME:

DATE:

TYPE:



CALI CEILING MOUNT

- **DLC Listed**
- **IP67 Rated**

ATG's CALI Garage Luminaire is a low-profile exterior luminaire designed for safe, reliable illumination from low to medium ceiling heights. The CALI is ideal for gas stations, parking garages, stairwells, entryways, and building overhangs. The garage luminaire is IP65 rated and may be deployed in ambient temperature ranges of -40° to 40°C.

CONSTRUCTION

The CALI LED light is manufactured within precise tolerances from heavy-wall, die-cast aluminum. Heat management is integral to the design and facilitates the unit's excellent functional life. The luminaire is rated for use in wet locations and can be operated at temperatures from -40° to 40°C.

OPTICS

Visual acuity is top-of-class with CRI of 80+. The lens is high-transmittance, prismatic acrylic that offers excellent protection and consistent optical performance. The luminaire is available in a standard color temperature 5000K, ideal for outdoor illumination. 3000K and 3500K models are available for direct factor order. The range of CCT options allows installers to design for a variety of functions.

ELECTRICAL

The luminaire draws 56W for a lumen output of 5,468 LM. Input voltage is a standard 100-277V and fixture lifespan is rated for 50,000 hours or greater, equivalent to 12 years of function at 12 hours per night. Sensors and controls can be easily added to extend longevity and facilitate smart functionality.

MOUNTING

The luminaire's features simple, direct mounting to standard 4" electrical boxes. Quick mount brackets for pendant mounting are also available.

STANDARD FEATURES

OPTIONS

FINISH



Sample Order: CL55-55-50-Z						
SERIES	WATTAGE	CCT	VOLTAGE	OPTICS	FINISH COLOR	OPTIONS
CL55=CALI	-48=48W	-50=5000K	Blank=120-277V -V=347-480V	Blank=Type V	-Z=Bronze	SF=Single Fuse, DF=Double Fuse

Performance Data								
PART NO.	WATTS(W)	INPUT VOLTAGE(VAC)	EFFICACY(Lm/W)	LUMENS(Lm)	CRI	CCT (K)	L70 (Hours)	DIMENSIONS (L*W*H) (Inches)
CL55	55.8	120-277	98.32	5,486	80+	5000	50,000	13.75*11.25*2.5

