

### Product Features:

- Smallest Form Factor in Mogul-Base Category
- Integrated 4kA/4kV Surge Protection
- Step-Down Thermal Management Protection
  - Wattage step-down circuit automatically prevents overheating due to high increases in ambient temperatures. Wattage returns to normal as temperatures decrease.
- Omni-directional
- Rated for Fully Enclosed Fixtures
- Wet Location Approved
- Special Adapter Transforms Base from E26 to E39
- Direct Retrofit for HID & CFL Fixtures

### Product Specifications:

Selectable Power: 9 Watts, 12 Watts, 18 Watts  
 Lamp Lumen Output: Up to 2,615 Lumens  
 Lamp Efficacy (lm/W): Up to 145 Lumens per Watt  
 Selectable Kelvin: 3000K, 4000K, 5000K  
 Dimensions:  
 (E26) 2.36"Ø x 6.73"  
 (EX39) 2.36"Ø x 6.77"  
 CRI: >80  
 Input Voltage: 120–277 VAC  
 Life Span: 50,000 Hours  
 Beam Angle: 300°  
 Base Types:  
 S-M (E26 with E39 adapter)  
 EX39  
 Operating Temperature: -40°F~140°F(-40°C~60°C)  
 Power Factor: >0.95  
 Total Harmonic Distortion (THD): < 20%



**EXCLUSIVE**  
E39-E26 Adapter Included

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



**SELECTABLE WATTS**  
9W, 12W, or 18W



**SELECTABLE KELVIN**  
3000K, 4000K or 5000K



**WATTAGE**  
SELECTABLE

**KELVIN**  
SELECTABLE



No Fans



No Noise



No Bugs



**Ordering Guide:**

ESL	-	TYPE	-	SELECTABLE WATTAGE	-	GENERATION	-	SELECTABLE KELVIN	-	BASE
ESL	-	CL (CL) Corn Light	-	0918W 9 Watts, 12 Watts, 18 Watts	-	5 (5) 5th Generation	-	3050 3000K, 4000K, 5000K	-	VV (S-M) E26/ (EX39) EX39

**Catalog Data:**

ITEM#	SELECTABLE WATTAGE	MAX LUMEN OUTPUT	MAX EFFICACY (lm/W)	SELECTABLE KELVIN
ESL-CL-0918W-53050-S-M ESL-CL-0918W-53050-EX39	9W, 12W, 18W	Up to 2,615	Up to 145	3000K, 4000K, 5000K
ESL-CL-1227W-53050-S-M ESL-CL-1227W-53050-EX39	12W, 18W, 27W	Up to 3,915	Up to 145	3000K, 4000K, 5000K

**Product Dimensions:**

