

Product Features:

- Smallest Form Factor in Mogul-Base Category
- Integrated 4kA/4kV Surge Protection
- Step-Down Thermal Management Protection
 - Wattage step-down circuit automatically prevents overheating due to high increases in ambient temperatures. Wattage returns to normal as temperatures decrease.
- Omni-directional
- Rated for Fully Enclosed Fixtures
- Wet Location Approved
- Special Adapter Transforms Base from E26 to E39
- Direct Retrofit for HID & CFL Fixtures — For use in:
 - Low Bays
 - Flood Lights
 - Wall Packs
 - Post Tops
 - And More!

Product Specifications:

Power: 80 Watts
 Lamp Lumen Output: Up to 10,400 Lumens
 Lamp Efficacy (lm/W): Up to 130 Lumens per Watt
 Selectable Kelvin: 3000K, 4000K, 5000K
 Dimensions: 5.12"Ø x 9.88"
 CRI: >80
 Input Voltage: 120–277 VAC
 Life Span: 50,000 Hours
 Beam Angle: 300°
 Base Type: EX39
 Operating Temperature: -4 ~ 149°F (-20 ~ 65°C)
 Power Factor: >0.95
 Total Harmonic Distortion (THD): < 20%

Project: _____

Date: _____

Catalog #: _____

Notes: _____



SELECTABLE KELVIN
3000K, 4000K or 5000K

Available Accessories:



Daylight / Occupancy
ESL-3DHOC-LV

KELVIN
SELECTABLE



No Fans



No Noise



No Bugs



Ordering Guide:

ESL	-	TYPE	-	WATTAGE	-	GENERATION	-	ADJUSTABLE KELVIN	-	BASE
ESL	-	CL	-	80W	-	5	-	3050	-	vv
		(CL) Corn Light		80 Watts		(5) 5th Generation		3000K, 4000K, 5000K		(EX39) EX39

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	SELECTABLE KELVIN
ESL-CL-36W-53050-S-M ESL-CL-36W-53050-EX39	36	4,680	130	3000K, 4000K, 5000K
ESL-CL-46W-53050-S-M ESL-CL-46W-53050-EX39	46	5,980	130	3000K, 4000K, 5000K
ESL-CL-55W-53050-S-M ESL-CL-55W-53050-EX39	55	7,150	130	3000K, 4000K, 5000K
ESL-CL-80W-53050-EX39	80	10,400	130	3000K, 4000K, 5000K
ESL-CL-120W-53050-EX39	120	15,600	130	3000K, 4000K, 5000K

Product Dimensions:

