

### FEATURES & SPECIFICATIONS

#### INTENDED USE

Premium grade, designer, shallow, surface mounted wraparound luminaire.  
For use in indoor application where aesthetics and quality are important, such as kitchens, recreation rooms, nursing homes, retail stores, and office areas.  
Regressed housing provides a floating appearance

#### SIZE W x L x H in inches (mm)

- 9.75W x 50.0L x 3.375H  
- 13.75W x 50.0L x 3.375H

#### MOUNTING

Mounts over electrical junction box. Offset mounting pads which keeps luminaire level and slightly off of mounting surface, are formed within the housing. Mounting holes are provided within offset to prevent distortion of housing when tightening mounting fasteners.



#### CONSTRUCTION

Die formed and spot welded, 22 gauge cold rolled steel housing. Spot-welded for rigidity and clean appearance. Ballast cover snaps into place eliminating the need for tools when accessing the ballast. Diffuser hinges from either side in a lift and shift manner and is self centering.

#### DIFFUSER

Specially formed plastic diffuser produces flawless light source with even illumination on all sides, and no distracting dark spots. Invisible hanging clips permit removal of lens from either side.

### ORDERING INFORMATION

Example: CLMMW248LF32W3450LDMV40K

#### STANDARD

CLM	MW	2	48L	F32W3450L	DMV	40K
<b>Series</b>		<b>Width</b>	<b>Size</b>	<b>Wattage and Lumen</b>		<b>Color Temperature</b>
CLM Contemporary CLOUD		2    9.75" 4    13.75"	48L    48"	F32W3450L    32 System Watts, 3450 Delivered Lumens F48W4800L    48 System Watts, 4800 Delivered Lumens F57W5400L    57 System Watts, 5400 Delivered Lumens		30K    3000K 35K    3500K 40K    4000K 50K    5000K
	<b>Lens Material</b>				<b>Driver</b>	
	MW    Matte White Acrylic				DMV    0-10V Dimming *Field installed-Dimming Wire DMVFID 0-10V Dimming *Factory installed-Dimming Wire	

#### HIGH OUTPUT

CLM	MW	2	48L	H72W7000L	DMV	40K
<b>Series</b>		<b>Width</b>	<b>Size</b>	<b>Wattage and Lumen</b>		<b>Color Temperature</b>
CLM Contemporary CLOUD		2    9.75" 4    13.75"	48L    48"	H72W7000L*    72 System Watts, 7000 Delivered Lumens		30K    3000K 35K    3500K 40K    4000K 50K    5000K
	<b>Lens Material</b>				<b>Driver</b>	
	MW    Matte White Acrylic				DMV    0-10V Dimming *Field installed-Dimming Wire DMVFID 0-10V Dimming *Factory installed-Dimming Wire	

\*Consult for more options