CRLX SERIES COMMERCIAL INDOOR LIGHTING



CRLX10-50-80W-MP


X GEN. LED COMMERCIAL RECESSED LIGHT





Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Customer Name: Project Name: Note: Type:



8 8/9"(H) X 11" (W) Mounting Diameters: 10"- 10.7"

Features

- 10" Haze Finish TRIM
- MCTP: The switch is on the light engine
- Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

Voltage: 120-277VAC 50/60Hz
Wattage: 50W/65W/80W
Power factor: >0.90
Efficacy: 85 LPW

Mechanical:

- 10" Haze Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCTP: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 6800LM Max.Color temperature: 3000K/3500K/4000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

 Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Other Models:

40W | 3400LM | CRLX10-18-40W-MCTP-D











Other Views:





CRLX-EGN-18-40W-MCTP Light Engine



CRLX-TRM-10 Trim



CRLX10-50-80W-MP Complete Unit

Performance Table: CRLX10-50-80W-MP

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLX10-50-80W-MP	50W	120-277V	4250LM	3000K 3500K 4000K	B1-U1-G0	85
	65W		5525LM			
	80W		6800LM			

2

Sample Ordering

Model Watt			Watt	Color Temp.		
CRLX10 =	50	_	80W	_	MP	

Factory-Installed Option:

Blank = No Option For Accessories
OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

Factory-Installed Option:





