

Series C

LED Medium Body Strip



FEATURES & SPECIFICATIONS

INTENDED USE

Medium body strip for interior warehouse, retail, and utility areas requiring general illumination in a commercial quality strip configuration.

SIZE W x L x H in inches

4.25W x 24"/48"/96"L x 2.00H

MATERIALS & FEATURES

Housing is die-formed and embossed code 22 gage steel. Finish is high reflectance baked white enamel. Wiring knockouts are provided on back and end of housing. Ballast covers or reflectors attach without tools to simplify ballast access.

See IND Series for similar fixtures with reflectors.

- End plate doubles as coupler for continuous row mounts.
- See IND Series for similar fixtures with reflectors.

MOUNTING

Surface mount, chain hung, double stem.

TYPICAL OPTIONS AND ACCESSORIES

Whips, Emergency battery backup (IOTA ILB-CP10), or contact factory for more details.

Listing

ETL Dry and Damp location rating.



2 ft - STANDARD

Example: C48LF30W3900LDMV40K

C	24L	F30W3900L	DMV	40K		
Series	Length	Wattage and Lumen		Driver	Kelvin Temperature	
C	24L 24"	F18W2500L	18 System Watts, 2500 Delivered Lumens	DMV 0-10V Dimming	30K	3000K
Medium Body Strip		F24W3350L	24 System Watts, 3350 Delivered Lumens		35K	3500K
		F28W3700L	28 System Watts, 3700 Delivered Lumens		40K	4000K
		F30W3900L	30 System Watts, 3900 Delivered Lumens		50K	5000K
					Options	
					WP	6 ft. 3 wire 18 gauge whip
					WP10	6 ft. 4 wire 18 gauge whip
					PI1	3 Wire Harness
					PI3	5 Wire Harness

4 ft - STANDARD

Example: C48LF35W4900LDMV40K

C	48L	F35W4900L	DMV	40K		
Series	Length	Wattage and Lumen		Driver	Kelvin Temperature	
C	48L 48"	F24W3500L	24 System Watts, 3500 Delivered Lumens	DMV 0-10V Dimming	30K	3000K
Medium Body Strip		F30W4300L	30 System Watts, 4300 Delivered Lumens		35K	3500K
		F35W4900L	35 System Watts, 4900 Delivered Lumens		40K	4000K
		F48W6500L	48 System Watts, 6500 Delivered Lumens		50K	5000K
		F57W7800L	57 System Watts, 7800 Delivered Lumens		Options	
					WP	6 ft. 3 wire 18 gauge whip
					WP10	6 ft. 4 wire 18 gauge whip
					PI1	3 Wire Harness
					PI3	5 Wire Harness



8 ft - STANDARD

Example: C96LF57W7800LDMV40K

C	96L	F57W7800L	DMV	40K		
Series	Length	Wattage and Lumen		Driver	Kelvin Temperature	
C Medium Body Strip	96L 96"	F24W3500L	24 System Watts, 3500 Delivered Lumens	DMV 0-10V Dimming	30K	3000K
		F48W6500L	48 System Watts, 6500 Delivered Lumens		35K	3500K
		F57W7800L	57 System Watts, 7800 Delivered Lumens		40K	4000K
		F70W9800L	70 System Watts, 9800 Delivered Lumens		50K	5000K
		F97W13000L	97 System Watts, 13000 Delivered Lumens		Options WP 6 ft. 3 wire 18 gauge whip WP10 6 ft. 4 wire 18 gauge whip PII 3 Wire Harness PI3 5 Wire Harness	
		F118W15500L	118 System Watts, 15500 Delivered Lumens			



DIMENSIONS

All dimensions are inches. Specifications subject to change without notice.

