


LED Ringed Ceiling Fixture

DIMENSIONS



APPLICATION

The LED Based DCR series is a ceiling or wall mount series which can be used in a broad range of residential and commercial applications. This series provides customers with a high quality luminaire utilizing the latest LED, solid state lighting and electronic driver technology for optimal performance and maximized energy efficiency. With a traditional opal white lens, the DCR series produces even, uniform light distribution and ideal choice for offices, corridors, stairways, bedroom, closet and foyers applications where customers are replacing incandescent, circline or compact fluorescent lamps.

FEATURES

- High-transmission (White) Acrylic lens with excellent distribution and uniformity.
- Full distribution LED Luminaire
- 10-100% triac dimming, compatible with most triac dimming switches in the market
- Designed for a 50,000 Hour Life
- Available in 3000K Kelvin color temperature
- Environmentally friendly - contains no mercury or other hazardous

HOUSING

Contemporary slyed fixture. Twin steel rings surround a milk white acrylic diffuse provides widespread and even illumination

MOUNTING

Designed for mounting on 4" electrical

ELECTRICAL

Equipped standard with 120V 15-100% triac dimming driver.

LISTING

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards.

WARRANTY

3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

QUICK SHIP

DCR-12-13-120D-930-NS
DCR-14-17-120D-930-NS

ORDERING INFORMATION

Example Model Number: DCR-12-13-120D-930-NS

DCR						
SERIES	SIZE	WATTAGE	DRIVER TYPE	COLOR TEMPERATURE	FINISH	OPTIONS
	12- 12" Pan 14- 14" Pan 16- 16" ¹	12" Pan 13- 13W, 1000 Lumens ² 14" Pan 17- 17W, 1700 Lumens ² 26- 26W, 2600 Lumens ²	120D- 120V, Triac Dimming ² MV- 120-277V ²	930- 90 CRI; 3000Kelvin ² 940-90 CRI; 4000 Kelvin ¹	NS- Nickel Satin ² ORB- Oil Rubbed Bronze ^{1 2}	MOS- Integral Microwave Sensor EML8- Emergency Battery Pack, 800 Lumens EML14- Emergency Battery Pack, 1400 Lumens

Notes:

¹Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.

²Energy star listed