



**JOB NAME:**

**CAT#:**

**TYPE:**

**APPLICATIONS**

A direct/indirect fixture that makes a bold statement by complementing design elements such as stone, metal, brick, and glass. The industrial look provides a modern aesthetic. It is available standard in white finish, and mounts with a cable kit. The louver is matte silver anodized parabolic.

**FEATURES & BENEFITS**

- Available standard in white finish or powder coated black
- Mounts with cable kit
- cETL<sub>US</sub> listed
- 5 year warranty

**DIMENSIONS**

48.0"L x 6.0"W x 5.25"H



Dimensions and specifications subject to change without notice.





**JOB NAME:**

**CAT#:**

**TYPE:**

**ORDERING**

EXAMPLE: DLV6 48 LED 48 DMV WH 40 H4W5

DLV6		LED								
1. SERIES	2. LENGTH	3. GEAR	4. WATTAGE/LUMENS		5. DRIVER	6. FINISH	7. COLOR TEMP			
DLV6	48	48" long	<b>48 inch</b>		DMV	120-277V Multivolt 0-10V Dimmable	WH	White	30	3000K
	96	96" long	24	24W 2800 Lumens				SI	Silver	35
		LED	48	48W 5650 Lumens	SDMV	Step dimming Multivolt	BK	Black	40	4000K
			57	57W 6400 Lumens				LUT	Lutron Driver <sup>1</sup>	BZ
			72	72W 8200 Lumens			GV			
			<b>96 inch</b>							
			48	48W 5650 Lumens						
			97	97W 11300 Lumens						
			114	114W 12800 Lumens						
			144	144W 16450 Lumens						

**8. EM(O)<sup>2</sup>**

**EM** Emergency Battery Pack 10W ~ 1700 lumens  
**EM5** Emergency Battery Pack 5W ~ 850 Lumens

**9. HANGING KIT(O)<sup>2</sup>**

**H4W** Cable kit with 4 cable + power feed cable incl. w/ white canopy  
**H4W5** Cable kit with 4' cable + power feed 0-10V dimming cable included w/ white canopy (5 wire)  
**H12W** Cable kit w/ 12' cable + power feed cable incl.w/ white canopy  
**H12W5** Cable kit w/ 12' cable + power feed 0-10V dimming. Cable included with white canopy (5 wire)  
**2SCS24WH** Two stem kits with 24" stem, canopy, and mounting hardware for a 4' fixture

**Cord & Whip Ordering Chart (Add to End of Fixture Part Number)**

Part No.	# of Wires	Length	End Fitting	Finish	Voltage	Amps (TL Only)
WP - Whip CS - Cord-set	(Blank) 3 Wire 4 - 4 Wire 5 - 5 Wire 6 - 6 Wire	(Blank) 6 feet 8 - 8 feet 10 - 10 feet 12 - 12 feet 15 - 15 feet	(Blank) No Plug P* - Standard Plug TL* - Twist Lock	BK - Black WH - White	(Blank) 120-277V 120 - 120V 277 - 277V 347 - 347V 480 - 480V	15 - 15 Amps 20 - 20 Amps

**Notes:**

<sup>1</sup>See Lutron Chart for Driver & Controls Options

<sup>2</sup>O is Optional

Dimensions and specifications subject to change without notice.

