

# 3-4098

## Wall Mount, Outdoor



### Features

#### Housing

Die-cast Aluminum with Powder Coated Finish  
 Finish Option: -06 White

#### Electrical

High Power Factor, Low THD  
 Built-in with or without Photo Cell

#### Lamp


Built-in LED Module: More Color Temperature Option - 4000K, 5000K  
 GU24 CFL Type: More Color Temperature Option - 2700K, 4000K

#### Certification

UL/cUL, ETL/cETL Listed

#### Warranty

5 Years Warranty on LED Driver and Module



### Built-in LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Shade	Dimension (H x W X E)	Energy Star	ETL Rated	Note
3-4098D-xxxxK	120V	15W	3000K / 80	800	PC	12.1" x 10.1" x 4.8"	Yes	Damp Location	
3-4098D-xxxxK-11W	120V	11W	3000K / 80	500	PC	12.1" x 10.1" x 4.8"	Yes	Wet Location	Driver On Board

### GU24 Type

Model	Input Voltage	Input Wattage	Finish	Shade	Lamp	Dimension (H x W X E)	Energy Star	UL Rated
3-4098PG-05	120V	18W	Black	PC	1 x 18W GU24	12.3" x 10.1" x 4.8"	---	Damp Location

Order Code: -PC Photo Cell