

C2018D-A C2024D-A

Ceiling Fixture & Pendant



Features

Housing

Die-formed Cold-rolled Steel

Finish Option: -08 Gray, -09 Silver, 22 Gold, -23 Light Gold, -30 Oil Rubbed Bronze, -05 Black

Ceiling Mount or Pendant Mount

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Lamp

LED Type: Built-in (Color Temperature Option – 3000K, 4000K)

Certifications

ETL/cETL Listed, Damp Locations Rated

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Wattage	LED CT	Lumen (Typ)	CRI	Finish	Shade	Dimension (OD X H)
C2018D-A-xxxxK-05/22	120V ~ 277V	35W	3000K or 4000K	1900	> 80	Black/Gold	Acrylic	18.0" x 4.5"
C2024D-A-xxxxK-05/22	120V ~ 277V	47W	3000K or 4000k	3200	> 80	Black/Gold	Acrylic	24.0" x 4.5"

Pendant / LED Type

Model	Input Voltage	Input Wattage	LED CT	Lumen (Typ)	CRI	Finish	Shade	Dimension (OD X H)
C2018D-A-PD-xxxxK-05/22	120V ~ 277V	35W	3000K or 4000K	1900	> 80	Black/Gold	Acrylic	18.0" x 11.5"
C2024D-A-PD-xxxxK-05/22	120V ~ 277V	47W	3000K or 4000K	3200	> 80	Black/Gold	Acrylic	24.0" x 11.5"