

DC913 DC916

Ceiling Fixture



Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

Electrical

High Power Factor, Low THD

Lamp


Built-in LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light
Color Temperature Option – 3000K, 3500K, 4000K, 5000K

Certifications

ETL/cETL Listed, Suitable for Damp Locations, Energy Star

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Voltage	LED CT	CRI	Lumen (Typ)	Dimension (L X W X H)	Finish	Energy Star
DC913D-62-3000K	120V ~ 277V	21W	3000K	> 80	1750	13.0" x 13.0" x 5.1"	Satin Nickel	Yes
DC913D-62-4000K	120V ~ 277V	21W	4000K	> 80	1850	13.0" x 13.0" x 5.1"	Satin Nickel	Yes
DC916D-62-000K	120V ~ 277V	35W	3000K	> 80	2900	16.0" x 16.0" x 5.4"	Satin Nickel	Yes
DC916D-62-4000K	120V ~ 277V	35W	4000K	> 80	3000	16.0" x 16.0" x 5.4"	Satin Nickel	Yes