



## WALLPACK : FULL CUTOFF

### DESCRIPTION

A compact, efficient, trapezoidal wallpack light featuring full cutoff optics for night sky friendliness.

### FEATURES

- Latest generation of LED chips delivers a similar light output to a 175, 250, or 400W metal halide using only 1/3 the energy consumption
- Full cutoff optics prevents neighborhood light trespass

### LISTINGS

- UL Listed for wet locations
- IP65 Rated
- IC Protection
- DesignLights Consortium® Qualified - meets DLC requirements for efficacy and lumen maintenance

### LED CHARACTERISTICS

- Rated lifetime L70: 50,000 hours
- 4000K/5000K CCT
- CRI: 80+

### ELECTRICAL

- Input voltage: 120-277V
- 0-10V dimming
- Power Factor: >.90
- THD: <20%

### CONSTRUCTION

- Die-cast aluminum body
- -40°F to 113°F (-40°C to 45°C) operating temperature

### WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date



### APPLICATIONS

- Industrial Parks
- Loading Docks
- Utility Sheds
- Entryways
- Walkways
- Storage Areas
- Security



## ORDERING INFORMATION

EXAMPLE: WPT-488-40W-840-UD-BZ

Model	Lumens	Watts	CRI/CCT	Voltage	Dimming	Finish
WPT : LED Full Cutoff Wallpack Trapezoid	488 - 4,880 lm	40W - 40W	840 - 80 CRI; 4000K	U - 120-277V	D - 0-10V Dimming	BZ - Bronze
	996 - 9,960 lm	80W - 80W	850 - 80 CRI; 5000K			

## PERFORMANCE SUMMARY

Order Code	Item #	Watts	Lumens	CCT	CRI	Volts	Replaces HID	DLC
11120	WPT-488-40W-840-UD-BZ	40W	4,880	4000K	80+	120-277V	175-250W	✓
11121	WPT-488-40W-850-UD-BZ	40W	4,880	5000K	80+	120-277V	175-250W	✓
11122	WPT-996-80W-840-UD-BZ	80W	9,960	4000K	80+	120-277V	250-400W	✓
11123	WPT-996-80W-850-UD-BZ	80W	9,960	5000K	80+	120-277V	250-400W	✓

\*Special order only. ✓DesignLights Consortium Qualified

## AVAILABLE ACCESSORIES

Order Code	Item #	Description
09966	PC1-4036-U	Photocell, Flush Mount, 120-277V
09967	PC1-4136-U	Photocell, Stem Mount, Side Lens, 120-277V
09968	PC1-4236-U	Photocell, Stem Swivel Mount, Side Lens, 120-277V
09969	PC1-4736-U	Photocell, Stem Swivel Mount, Top Lens, 120-277V

## DIMENSIONS

