

E2-WP10

FULL CUT-OFF WALL PACK

30W 40W 60W 80W
with 2-in-1 Motion Sensor / Photocell & Emergency Battery Backup

NEW

PRODUCT DESCRIPTION:

FALKOR LIGHTING's Full Cut-Off Wall Pack is a highly efficient, multi-function fixture that provides a long-lasting and energy saving lighting solution. This fixture comes equipped with a Plug & Play 2-in-1 microwave motion sensor and daylight harvesting photocell; along with an integrated emergency backup battery that delivers at least 90 min. of emergency light in the event of power loss. The rugged housing offers advanced thermal management and protection against outdoor environments without compromising aesthetics.

FEATURES AND STANDARDS:

- ETL/cETL/DLC premium certificate.
- Easy installation.
- Wet location rated IP65.
- Durable die-cast aluminum housing.
- Photocell and motion sensor options.
- UV-resistant polycarbonate refractor lens.
- Emergency power 4W - 30W and 40W & 10W - 60W and higher wattage operating time 1.5 hours.
- Type III distribution optics standard/ Other optics available by request.

APPLICATION:

Outdoor wall-mount applications: building facade, commercial, industrial, retail, hospitality buildings that demand long service life and low maintenance.

TESTED DATA:

- Input Power - 30W,40W,60W,80W
- Lumen - 3900,5200,7800,10400lm
- Efficacy - 130LM/W (±10%)
- Input Voltage - 120-277VAC
- Color Temperature - 5000K
- THD - <20%
- Dimmable - 0-10V
- LED Brand - Lumileds
- LED Type - 3030
- LED QTY - 48,48,72,96 pcs
- Viewing Angle - Type III
- Operating Temperature - 86°F to 113°F (-30°C to +45°C)
- Operating Humidity - RH<90%
- Color Rendering Index - Ra>70
- IP Rating - IP65
- Certification - cETL/ETL/DLC Premium
- Housing - Die-cast Aluminum
- Life Time - >50,000Hrs
- Warranty - 5 Years

Good heat dissipation, light weight, cost-effective and low transportation cost.


UV-resistant polycarbonate refractor lens.

Emergency Battery Backup test button & indicator light.

Plug & Play sensor with microwave and daylight harvesting function, 2-in-1 sensor.

Built in level

EVA foam for good sealing



4W battery - 30W & 40W fixtures





10W battery - 60W & 80W fixtures





Product Number	Wattage	Color	Certifications	Dimmable	Voltage	Lumens	Working Hours	CRI
E2-WP10-30W-50-E-M/P	30W	5000K	cETL/ETL/DLC Premium	0-10V	120-277Vac	3900lm	50,000hrs	Ra>70
E2-WP10-40W-50-E-M/P	40W	5000K	cETL/ETL/DLC Premium	0-10V	120-277Vac	5200lm	50,000hrs	Ra>70
E2-WP10-60W-50-E-M/P	60W	5000K	cETL/ETL/DLC Premium	0-10V	120-277Vac	7800lm	50,000hrs	Ra>70
E2-WP10-80W-50-E-M/P	80W	5000K	cETL/ETL/DLC Premium	0-10V	120-277Vac	10400lm	50,000hrs	Ra>70

DIMMENSIONS:



30-40W



60-80W

