



## **Economy Channel Standard (NO Ballast)**

Specifications • Snap-on components for easy assembly and maintenance • Versatile end plate doubles as coupler for continuous row mounting • Available in lengths from 18 to 96 inches • Surface, stem or chain mountable • Fixture is wired for LED Bulbs. No Ballast included Applications Fluorescent channel fixture. For use in indoor applications such as factories, warehouses, workshops, utility areas, coves and public buildings. Additional Features • With Plug



### **General Characteristics**

**Material**

**Bulb**

**Finish**

**Base**

**Safety Rating**

Steel

T8

White

Medium 2-Pin (G13)

ETL Listed

### **Fixture Characteristics**

**Collection**

**Style**

**Shape**

**Number of Lights**

**Bulb Max Wattage**

**Mounting**

**Use Location**

Bypass

Traditional

Linear

2 - Light

17 Max

Surface

Indoor

### **Electrical Characteristics**

**Watts**

**Volts**

2x 17

Multi-Volt

### **Product Dimensions**

**Size**

**Item Dimensions (in)**

24"

(W) 4.25 (H) 1.88 (D) 24.00

### **Product Data**

**Item Number**

**Case Quantity**

**Barcode on SKU**

**Brand**

**Description**

92118-SU

1

653703921181

SUNLITE

EC-2-F17T8