



## **Economy Channel Standard (NO Ballast)**

Specifications• Snap-on components for easy assembly and maintenance• Versatile end plate doubles as coupler for continuous row mounting• Available in lengths from 18 to 96 inches• Surface, stem or chain mountable• Fixture is wired for LED Bulbs. No Ballast includedApplicationsFluorescent channel fixture. For use in indoor applications such as: factories, warehouses, workshops, utility areas, coves and public buildings.



### **General Characteristics**

**Material**

**Bulb**

**Finish**

**Base**

**Safety Rating**

Steel

T8

White

Medium 2-Pin (G13)

ETL Listed

### **Fixture Characteristics**

**Collection**

**Style**

**Shape**

**Number of Lights**

**Bulb Max Wattage**

**Mounting**

**Use Location**

Bypass

Traditional

Linear

2 - Light

32 Max

Surface

Indoor

### **Electrical Characteristics**

**Watts**

**Volts**

2x 32

Multi-Volt

### **Product Dimensions**

**Size**

**Item Dimensions (in)**

48"

(W) 4.25 (H) 1.88 (D) 48.00

### **Product Data**

**Item Number**

**Case Quantity**

**Barcode on SKU**

**Brand**

**Description**

92034-SU

1

653703920344

SUNLITE

EC-2-F32T8