

**20 Amp 125Volt Plug
NEMA L5-20P**



Model No.: 66401-BK

Description: Enerlites's NEMA devices provide a safe disconnect solution between an equipment load and a power source. Built of durable thermoplastic, Locking plugs have the pins arrayed in a circular manner. The plug is inserted into the female side and twisted to lock in place. To ensure correct and speedy wiring, terminals have ID markings.

Features:

- Terminals marked for easy identification and fast wiring
- Visible stamped NEMA configuration and device rating.

Specifications:

Type.....	Plug
Rating.....	20Amp, 125Volt
Wiring Scheme.....	2 Pole, 3 Wire
Nema Configuration.....	L5-20P
Max Working Voltage.....	20Amp
Termination.....	4AWG Conductors
Cord Range.....	.28" - .88"
Wire Gauge.....	14-10AWG
Standards and Certifications.....	UL Listed

20AMP 125V
2-Pole 3-Wire Grounding,
L5-20



Receptacle
L5-20R



Plug
L5-20P



Connector
L5-20C



Flanged Inlet
L5-20PF1



Flanged Outlet
L5-20RFO

Testing & Code Compliance



Enerlites, Inc.

www.enerlites.com

Phone: 949-756-0536 Fax: 949-756-0528 e-mail: sales@enerlites.com