

**Industrial Grade
Locking Receptacle
NEMA L6-20R**



Model No.: 66410-BK

Description: Enerlites's locking devices provide a safe disconnect solution between an equipment load and a power source. These devices incorporate a locking interface that is engaged and disengaged simply by rotating the device assuring a safe and reliable electrical connection.

Features:

- Nylon Construction, Visible NEMA Ratings, Nickel Plated Receptacle Strap
- Flammability UL94, V2 Rating
- High Impact-Resistant Chemical-Resistant Nylon
- Reinforced Thermoplastic Polyester
- Ratings and NEMA identification are permanently marked on device.

Specifications:

Type.....	Locking devices
Rating.....	20Amp, 250Volt
Wiring Scheme.....	2 Pole, 3Wiring Grounding
Nema Configuration.....	L6-20R
Max Working Voltage.....	250VAC
Termination.....	#14 to #8 AWG Solid Copper Wire.
Contact Blade Material.....	Rivetless Copper Alloy
Standards and Certifications.....	UL Listed

20AMP 250V
2-Pole 3-Wire Grounding,
L6-20



Receptacle
L6-20R



Plug
L6-20P



Connector
L6-20C



Flanged Inlet
L6-20PFI



Flanged Outlet
L6-20RFO

Testing & Code Compliance



Enerlites, Inc.

www.enerlites.com

Phone: 949-756-0536 Fax: 949-756-0528 e-mail: sales@enerlites.com