



## Industrial Grade Locking Flanged Inlet, Grounding NEMA L14-30P

**Model No: 66493-W**

### Description

Enerlites's locking devices provide a safe disconnect solution between an equipment load and a power source. These devices incorporate a locking interface that is engaged and disengaged simply by rotating the device assuring a safe and reliable electrical connection. The nylon housing of insulated design shields exposed metal parts on hand-held side. The industrial strength contacts resist heat rise, provide excellent conductivity. The internal dust shield design keeps terminals free of contaminants.

### Features

- Flammability UL94, V2 Rating
- High Impact-Resistant Chemical-Resistant Nylon
- Reinforced Thermoplastic Polyester
- Ratings and NEMA identification are permanently marked on device.

### Specifications

Type	Locking Flanged Inlet
Rating	20Amp, 125/250Volt
Wiring Scheme	3 Pole, 4 Wire Grounding
NEMA Configuration	L14-30P
Max Working Voltage	125/250VAC
Termination	#10 AWG Solid Copper Wire

### Standards & Compliance



20AMP 125V  
2-Pole 3-Wire Grounding,  
L5-20



Receptacle  
L5-20R



Plug  
L5-20P



Connector  
L5-20C



Flanged Inlet  
L5-20PFI



Flanged Outlet  
L5-20RFO