

## Ultra-thin Downlight



## Project Name:


## Type:

## Catalog#

The EX-Lite DL is an ultra-thin direct installed LED down light that clips to the ceiling without a can. Three CCT 30K/40K/50K selectable all in one.

It delivers soft light for indoor commercial and residential lighting with its frosted lens.

| Model | Lumens | Power | lm/W    | сст               | CRI |
|-------|--------|-------|---------|-------------------|-----|
| DL4   | 700lm  | 9W    | 70+lm/W | 3000K/4000K/5000K | 90+ |
| DL6   | 1200lm | 14W   | 70+lm/W | 3000K/4000K/5000K | 90+ |





| ZONAL LUMEN SUMMARY |         |        |             |  |  |  |  |
|---------------------|---------|--------|-------------|--|--|--|--|
| ZONE L              | UMENS ( | % LAMP | % LUMINAIRE |  |  |  |  |
| 0-30                | 203.4   | 28.6%  | 28.6%       |  |  |  |  |
| 0-40                | 333.0   | 46.7%  | 46.7%       |  |  |  |  |
| 0-60                | 583.0   | 81.8%  | 81.8%       |  |  |  |  |
| 60-90               | 129.3   | 18.2%  | 18.2%       |  |  |  |  |
| 70-100              | 44.6    | 6.3%   | 6.3%        |  |  |  |  |
| 90-120              | 0.000   | 0%     | 0%          |  |  |  |  |
| 0-90                | 712.4   | 100%   | 100%        |  |  |  |  |
| 90-180              | 0.000   | 0%     | 0%          |  |  |  |  |
| 0-180               | 712.4   | 100%   | 100%        |  |  |  |  |

| ZONAL LUMEN SUMMARY |         |        |             |  |  |  |  |
|---------------------|---------|--------|-------------|--|--|--|--|
| ZONE                | LUMENS  | % LAMP | % LUMINAIRE |  |  |  |  |
| 0-30                | 332.5   | 27.9%  | 27.9%       |  |  |  |  |
| 0-40                | 545.2   | 45.7%  | 45.7%       |  |  |  |  |
| 0-60                | 960.1   | 80.4%  | 80.4%       |  |  |  |  |
| 60-90               | 233.4   | 19.6%  | 19.6%       |  |  |  |  |
| 70-100              | 88.3    | 7.4%   | 7.4%        |  |  |  |  |
| 90-120              | 0.000   | 0%     | 0%          |  |  |  |  |
| 0-90                | 1,193.6 | 100%   | 100%        |  |  |  |  |
| 90-180              | 0.000   | 0%     | 0%          |  |  |  |  |
| 0-180               | 1,193.6 | 100%   | 100%        |  |  |  |  |

**DL4 Polar & Lumen Summary** 

**DL6 Polar & Lumen Summary** 





DL6