





Project Name:

Type:

Catalog#:

The FL series is a heavy duty and low-profile LED flood light luminaire designed to fit any outdoor flood applications. Its on-chip optic helps focus the light in a much more efficient way.

It comes with Knuckle, Slipfitter and Yoke mounts.

Ordering SKU:

Family Model	Wattage	ССТ	Control	Color	Voltage
FL	15W =15W	30K =3000K	(blank)=none, Std	(blank)=Bronze, Std	(blank)=120/277VAC, Std
Flood Light	30W =30W	40K =4000K	PCB=Button Photocell	BL =Black	HV =347/480VAC
	50W =50W	50K =5000K		WH =White	
	70W =70W			GR =Gray	
	100W =100W				

Specs:

Family Model	Wattage	Lumens	lm/W	сст	CRI
FL-15W	15W	1,950lm	130lm/W	4000K/5000K	75+
FL-30W	30W	3,900lm	130lm/W	4000K/5000K	75+
FL-50W	50W	6,500lm	130lm/W	4000K/5000K	75+
FL-70W	70W	91,00lm	130lm/W	4000K/5000K	75+
FL-100W	100W	13,000lm	130lm/W	4000K/5000K	75+

Features & Specs

Construction:

- -Low profile architectural look.
- -Superior heat sinking with external Air-Flow fins.
- -IP65 for wet and damp locations.

Mounting:

- -1/2" Knuckle Mount.
- -2 3/8" Slipfitter Mount (for 70W & above).
- -Yoke Mount.

Electrical:

- -High Power Factor, low THD UL listed driver.
- -Universal line voltage input 120-277V, 347/480V optional.
- -FCC compliant.

Optical:

-On-Chip optic designed for better focusing without glare.

Controls Options:

-Button style eye photocell.

Warranty:

-5 years warranty for complete fixture.

Listings:

UL

DLC

RoHs

IP65












Photometrics:




Dimensions:








70W/100W Slipfitter



70W/100W Yoke



70W/100W Knuckle

	Α	В	С	D	E	F	G
FL-15W	5.1"	6.1"	3.3"	1.8"	5.7"	4.3"	1.5"
FL-30W	7.0"	7.2"	3.3"	2"	7.8"	6.5"	2.5"
FL-50W	9.0"	8.4"	2.2"	2.3"	9.8"	7.7"	2.6"