14 1/2"





### **General Description:**

The WPCL is a large size Cut-Off style wall pack designed to be Dark-Sky compliant.

A wide range of control options are available including Occ sensor, Photocell and Emergency backup.

#### **Construction:**

- -Heavy duty aluminum housing
- -Glare-free optic
- -IP65 for wet and damp locations

#### Mounting:

- Regular in-wall J-box

### **Electrical:**

- -High Power Factor, low THD UL listed driver with 5KV surge protection.
- -Universal line voltage input 120-277V, 347/480V optional
- -0-10V dimmable optional

### **Optical:**

-Glare-free Polycarbonate lens.

#### **Controls:**

- -Button style eye photocell.
- -Bi-Level Occupancy sensor.
- -Build-in emergency backup.

#### Warranty:

-5 years warranty for complete fixture

### **Listings:**

ETL DLC RoHs IP65









#### **Order Info:**

| Model                   | Wattage         | сст               | Control                     | Color               | Voltage                 |
|-------------------------|-----------------|-------------------|-----------------------------|---------------------|-------------------------|
| WPCL                    | <b>25W</b> =25W | <b>30K</b> =3000K | (blank)=none, Std           | (blank)=Bronze, Std | (blank)=120/277VAC, Std |
| Large Cut-Off Wall Pack | <b>40W</b> =40W | <b>40K</b> =4000K | PCB=Button Photocell        | <b>BL</b> =Black    | <b>HV</b> =347/480VAC   |
|                         | <b>60W</b> =60W | <b>50K</b> =5000K | OCC=Bi-Level Sensor         | <b>WH</b> =White    |                         |
|                         | <b>80W</b> =80W |                   | <b>EM</b> =Emergency Backup | <b>GR</b> =Gray     |                         |
|                         |                 |                   |                             |                     |                         |


| PROJECT NAME: | CATALOG NUMBER: |
|---------------|-----------------|
| NOTES:        | FIXTURE TYPE:   |




## Specs:

| Family Model | Wattage | Lumens   | lm/W    | сст               | CRI |
|--------------|---------|----------|---------|-------------------|-----|
| WPCL-25W     | 25W     | 3,250lm  | 130lm/W | 3000K/4000K/5000K | 70+ |
| WPCL-40W     | 40W     | 5,200lm  | 130lm/W | 3000K/4000K/5000K | 70+ |
| WPCL-60W     | 60W     | 7,800lm  | 130lm/W | 3000K/4000K/5000K | 70+ |
| WPCL-80W     | 80W     | 10,400lm | 130lm/W | 3000K/4000K/5000K | 70+ |

### **Photometrics:**





# **Lighting Layout:**

