


ME:	
	ME:

DATE: \_\_\_\_ TYPE:

#### **DIMENSIONS:**



2 1 /2//		10//1	~`
3-1/2"(	п) х	TQ (I	ור



VOLTAGE

120VAC

Dimming: Dimmable down to 10% using an approved

LUMENS

2200LM

COLOR TEMP

4000K

# FDL-18-30W-40K

# LED DRUM FIXTURES

The LED Flush Mount Surface Fixture is a low profile downlight intended for ceiling or wall mount applications. Driver on Board (DOB) technology, with no driver or transformer needed. These flush mount ceiling lights mount directly to a 4" deep dish junction box. Ideal for Residential and commercial applications.

#### **ELECTRICAL SPECIFICATIONS:**

- Voltage: 120VAC
- Wattage: 30W
- Power factor: >0.90
- Efficacy: 73LM/W

#### **HOUSING SPECIFICATIONS:**

- Construction: Spun aluminum (brushed nickel finish)
- Gasket: closed cell Neoprene foam gasket
- Suitable for damp locations when gasket is used
- Maximum Ambient temperature: 104°F

## **CERTIFICATIONS: ETL**





LED: Seoul DOB (Driver On Board) Technology

Optics: white translucent acrylic lens

WATTS

30W

Total lumens: 2200LM

MODEL FDL-18-30W-40K

• Color temperature: 4000k

**LIGHTING SPECIFICATIONS:** 

• CRI: >80

dimmer

•

•

•

## WARRANTY: 5 years