

## Features

### Housing

Injection Molded Polycarbonate  
 Stainless Steel Clips  
 Ideal for Harsh Environment Applications  
 Suitable for Ceiling Mount or Suspended Mount

### Optical

Shade: Injection Molded High Transmission Opal Polycarbonate Creates Excellent Light Distribution and Uniformity  
 High Luminous Efficacy > 100lm/W

### Electrical

Built-in Constant Current LED Driver with High efficient LED Module  
 Bi-Level Light Option - with Built-in Motion Sensor  
 Emergency Back Up Option - Built-in Emergency Battery Back Up

### Lamp

Built-in LED Module

### Certification

ETL/cETL Listed, DLC Listed

### Warranty

5 Years Warranty on Driver and LED Module



## LED Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L X W X H)	DLC
BH24DX-16W-4000K	120V ~ 277V	16W	4000K	80	1800	26.5" x 4.3" x 2.4"	Standard
BH24DX-16W-5000K	120V ~ 277V	16W	5000K	80	1850	26.5" x 4.3" x 2.4"	Standard
BH48DX-36W-4000K	120V ~ 277V	36W	4000K	80	3800	50.0" x 4.3" x 2.4"	Standard
BH48DX-36W-5000K	120V ~ 277V	36W	5000K	80	3900	50.0" x 4.3" x 2.4"	Standard
BH24DX-HE-4000K	120V ~ 277V	25W	4000K	80	2800	26.5" x 4.3" x 2.4"	Standard
BH24DX-HE-5000K	120V ~ 277V	25W	5000K	80	2900	26.5" x 4.3" x 2.4"	Standard
BH48DX-HE-4000K	120V ~ 277V	48W	4000K	80	5300	50.0" x 4.3" x 2.4"	Standard
BH48DX-HE-5000K	120V ~ 277V	48W	5000K	80	5500	50.0" x 4.3" x 2.4"	Standard
BH24DX-VHO-4000K	120V ~ 277V	16W	4000K	80	1800	26.5" x 4.3" x 2.4"	Premium
BH24DX-VHO-5000K	120V ~ 277V	16W	5000K	80	1850	26.5" x 4.3" x 2.4"	Premium
BH48DX-VHO-4000K	120V ~ 277V	32W	4000K	80	4085	50.0" x 4.3" x 2.4"	Premium
BH48DX-VHO-5000K	120V ~ 277V	32W	5000K	80	4290	50.0" x 4.3" x 2.4"	Premium