



HID LED lamp replaces a 70-400W HID and is suitable for use in totally enclosed fixtures. Its high lumen output and exceptional efficacy make it an ideal choice for outdoor post top applications. The special designed heat sink system allows air to flow freely through the lamp. It uses an increased cooling surface area to reduce the operating temperature of the LED and power supply, thus resulting in longer lamp life and lumen maintenance.

- 70W-400W HID replacement
- Direct line voltage 120-277V - Not compatible with ballasts
- Designed for use in post top applications
- Fully omni-directional
- Suitable for use in totally enclosed fixtures
- 5 years warranty
- DLC 4.4 Listed

Ordering Code	Watt (W)	Initial Lumen	Base **	CRI	Color Temp.	Rated Average life	MOD (in.)	MOL (in.)	DLC LISTED Y/N
CN[E39/EX39]-850-36P-M3-BP	36	5200	EX39	82	5000K	50,000	3.78	7.87	Y
CN[E39/EX39]-850-54P-M3-BP	54	7800	EX39	82	5000K	50,000	3.78	9.72	Y
CN[E39/EX39]-850-63P-M3-BP	63	9100	EX39	82	5000K	50,000	3.78	10.35	Y
CN[E39/EX39]-850-100P-M3-BP	100	14500	EX39	82	5000K	50,000	4.84	10.83	Y

** EX39 is compatible with E39 base

Note: This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause an undesired operation.

Suitable for use in enclosed luminaires. This device is not intended for use with emergency exits.